



What can we help you find?

- [Products](#)
- [Industries](#)
- [Resources](#)
- [About TE](#)
- [My Account](#)
- [Innovation](#)
- [Support Center](#)

1-1393217-6 Product Details

- [Share](#)
[Print](#)
[Email](#)



1-1393217-6

TE Internal Number: 1-1393217-6

✔ Active

Industrial Relays (General Purpose)

✔ Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- RE Series
- Contact - Current Class = 5A to 10A Class, Less Than 16A
- Contact - Rated Current = 6 A
- Terminal Type = PCB-THT
- Contact - Arrangement = 1 Form A (NO)

[View all Features](#)

Quick Links

- [▶ Pricing & Availability](#)
- [▶ Search for Tooling](#)
- [▶ Product Feature Selector](#)
- [▶ Contact Us About This Product](#)

- [Add to My Part List](#)
[Request Sample](#)
[Find Similar Products](#)
[Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Series = RE • Terminal Type = PCB-THT <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Contact - Current Class = 5A to 10A Class, Less Than 16A • Contact - Rated Current (A) = 6 • Contact - Limiting Continuous Current (A) = 6 • Contact - Limiting Making Current (A) = 15 • Contact - Limiting Breaking Current (A) = 6 • Insulation - Initial Dielectric Between Coil/Contact Class = 3500V to 4000V Class • Insulation - Initial Dielectric Between Open Contacts (V rms) = 1000 • Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 4000 • Contact - Rated Voltage (VAC) = 250 • Contact - Switching Voltage Max. (VAC) = 400 • Contact - Limiting Short-Time Current (A) = 6 • Coil - Rated Voltage (VDC) = 18 • Coil - Resistance (Ω) = 1620 • Coil - Rated Power, DC (mW) = 200 • Coil - Rated Power Class = 150mW to 200mW Class • Insulation - Initial Insulation Resistance (MΩ) = 1000000 • Insulation - Creepage Class = 3mm to 5.5mm Class • Insulation - Clearance Class = 2.5mm to 4mm Class • Insulation - Special Features = Tracking Index of Relay Base PT1250 <p>Dimensions:</p> <ul style="list-style-type: none"> • Mechanical - Length Class = 16mm to 20mm Class • Length (mm [in]) = 20.00 [0.787] 	<p>Body Features:</p> <ul style="list-style-type: none"> • Mount Type = PCB • Weight (g [oz]) = 5.00 [0.1764] <p>Contact Features:</p> <ul style="list-style-type: none"> • Contact Material = AgNi0.15 • Contact - Number of Poles = 1 <p>Configuration Features:</p> <ul style="list-style-type: none"> • Contact - Arrangement = 1 Form A (NO) • Coil - Magnetic System = Monostable, DC • Coil - Special Features = UL Coil Insulation Class F <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Wave solder capable to 260°C, Wave solder capable to 240°C • RoHS/ELV Compliance History = Always was RoHS compliant • Approved/Registered Standards = VDE, cULus, cCSAus <p>Environmental:</p> <ul style="list-style-type: none"> • Environmental - Category of Protection = RTIII • Environmental - Ambient Temperature, Max. (°C [°F]) = 70 [158] • Environmental - Ambient Temperature Class = 50°C to 70°C Class <p>Packaging Features:</p> <ul style="list-style-type: none"> • Packaging Method = Tube <p>Other:</p> <ul style="list-style-type: none"> • Brand = Schrack

- Mechanical - Width Class = 8mm to 10mm Class
- Width (mm [in]) = 10.00 [0.394]
- Mechanical - Height Class = 10mm to 11mm Class
- Height (mm [in]) = 10.60 [0.417]
- Insulation - Clearance Between Contact and Coil (mm [in]) = 4 [0.157]
- Insulation - Creepage Between Contact and Coil (mm [in]) = 4 [0.157]

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed

