



RTE24615 Product Details

[Share](#) | [Print](#) | [Email](#)


Industrial Relays (General Purpose)

[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- RT 2 Series
- Contact - Current Class = 5A to 10A Class, Less Than 16A
- Contact - Rated Current = 8 A
- Terminal Type = PCB-THT, Plug-in
- Contact - Arrangement = 2 Form C (CO)

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

RTE24615

(1-1393243-7)

TE Internal Number: 1-1393243-7

Active

[View 3D PDF](#)

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [Power PCB Relay RT2 \(PDF, English\)](#)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: (CAD Format & Compression Information)

- [2D Drawing \(DXF, Version C\)](#)
- [3D Model \(IGES, Version C\)](#)
- [3D Model \(STEP, Version C\)](#)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Electrical Characteristics:

- Contact - Current Class = 5A to 10A Class, Less Than 16A
- [Contact - Rated Current \(A\)](#) = 8
- Contact - Limiting Continuous Current (A) = 8
- Contact - Limiting Making Current (A) = 15
- Contact - Limiting Breaking Current (A) = 8
- Insulation - Initial Dielectric Between Coil/Contact Class = >4000V Class
- Insulation - Initial Dielectric Between Open Contacts (V rms) = 1000
- Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 5000
- Contact - Rated Voltage (VAC) = 250
- Contact - Switching Voltage Max. (VAC) = 400
- Contact - Limiting Short-Time Current (A) = 8
- Coil - Rated Voltage (VAC) = 115
- [Coil - Resistance \(Ω\)](#) = 8100
- [Coil - Rated Power, AC \(VA\)](#) = 1.00
- Coil - Rated Power Class = 0.5VAW to 1.0VA Class
- Insulation - Initial Dielectric Between Adjacent Contacts (V rms) = 2500
- Insulation - Creepage Class = >8mm Class
- Insulation - Clearance Class = >8mm Class
- Insulation - Special Features = Tracking Index of Relay Base PTI250

Dimensions:

- Mechanical - Length Class = 25mm to 30mm Class
- Length (mm [in]) = 29.00 [1.142]
- Mechanical - Width Class = 12mm to 16mm Class
- Width (mm [in]) = 12.70 [0.500]

Body Features:

- Mount Type = PCB, Socket
- Weight (g [oz]) = 13.00 [0.459]

Contact Features:

- Terminal Type = PCB-THT, Plug-in
- Contact Material = AgNi90/10
- Contact - Number of Poles = 2

Configuration Features:

- [Contact - Arrangement](#) = 2 Form C (CO)
- [Coil - Magnetic System](#) = Monostable, AC
- Coil - Special Features = UL Coil Insulation Class F

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 260°C, Wave solder capable to 240°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive
- Approved/Registered Standards = cCSAus, cULus, VDE

Environmental:

- Environmental - Category of Protection = RTIII
- Environmental - Ambient Temperature, Max. (°C [°F]) = 70 [158]
- Environmental - Ambient Temperature Class = 50°C to 70°C Class

Packaging Features:

- Packaging Method = Tube

Feedback

- Mechanical - Height Class = 15mm to 16mm Class
- Height (mm [in]) = 15.70 [0.618]
- Insulation - Clearance Between Contact and Coil (mm [in]) = 10 [0.394]
- Insulation - Creepage Between Contact and Coil (mm [in]) = 10 [0.394]

Other:

- Series = RT 2
- Brand = Schrack
- Accessories/Socket Type = DIN-rail Socket, PCB Socket

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)
- [AODA Multi-Year Accessibility Plan](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed

