



SIGNAL RELAYS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

IM02NS=IM RELAY 140 MW 4.5V

Axicom | IM

1-1462038-2

TE Internal Number: 1-1462038-2
Alias ID: AMP-1-1462038-2, CC3085-000

Always EU RoHS/ELV Compliant

Contact Voltage Rating **250 VAC [220 VDC]**

Coil Power Rating (DC) (mW) **140**

Isolation (HF Parameter) **-37dB @ 100MHz, -18.8dB @ 900MHz**

Insertion Loss (HF Parameter) **-.33dB @ 900MHz, -.03dB @ 100MHz**

Insulation Initial Resistance (MΩ) **1000000**

Product Drawings

IM-Relay Marking

PDF
English

IM2-N-Relay

PDF
English

CAD Files

3D PDF

PDF
3D

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Product Specifications

Product Specification

IM Relay Datasheet

PDF
English

Definitions Relays

PDF
English

Product Environmental Compliance

TE Material Declaration

MD_1-1462038-2_01012014824_dmtec

PDF
English

Drawing for all design activity.

Product Type Features	Product Type	Relay
	Relay Type	IM Relay
Electrical Characteristics	Contact Voltage Rating	250 VAC [220 VDC]
	Coil Power Rating (DC) (mW)	140
	Insulation Initial Resistance (MΩ)	1000000
	Coil Voltage Rating (VAC)	5
	Contact Switching Voltage (Max)	250 VAC [220 VDC]
	Coil Magnetic System	Monostable, DC
	Insulation Initial Dielectric Between Coil/Contact Class	1500 V – 2500 VA
	Insulation Initial Dielectric Between Adjacent Contacts (Vrms)	1000
	Insulation Initial Dielectric Between Contacts and Coil (Vrms)	1800
	Contact Limiting Making Current (A)	2
	Insulation Initial Dielectric Between Open Contacts (Vrms)	1000
	Actuating System	DC
	Contact Limiting Short-Time Current (A)	2
	Contact Limiting Continuous Current (A)	2
	Coil Resistance (Ω)	145
	Contact Switching Load (Min)	.1mA @ .0001V
	Contact Limiting Breaking Current (A)	2
	Coil Power Rating Class	50 – 300mW
	Coil Type	Monostable
	Voltage Standing Wave Ration (HF Parameter)	1.07 @ 100MHz, 1.45 @ 900MHz
Signal Characteristics	Isolation (HF Parameter)	-37dB @ 100MHz, -18.8dB @ 900MHz
	Insertion Loss (HF Parameter)	-.33dB @ 900MHz, -.03dB @ 100MHz
Body Features	Insulation Special Features	2500V Initial Surge Withstand Voltage between Contacts & Coil
	Weight (oz)	.75
Contact Features	Terminal Type	PCB-THT
	Contact Current Rating (A)	2
	Contact Arrangement	2 Form C (CO)

Contact Material	PdRu
Contact Number of Poles	2
Contact Special Features	Bifurcated/Twin Contacts
Contact Current Class	0 – 2 A
Contact Plating Material	Gold

Mechanical Attachment	Mounting Type	Printed Circuit Board
-----------------------	---------------	------------------------------

Dimensions	Length Class (Mechanical)	0 – 10 mm
	Width Class (Mechanical)	0 – 6 mm
	Length (in)	10
	Width	5.7 mm [.224 in]
	Height Class (Mechanical)	0 – 6 mm
	Dimensions (L x W x H) (Approximate)	10 x 5.7 x 5.8 mm [.393 x .236 x .228 in]
	Height	5.8 mm [.228 in]

Usage Conditions	Environmental Category of Protection	RTV
	Environmental Ambient Temperature (Max)	85 °C [85 °F]
	Environmental Ambient Temperature Class	70 – 85°C

Operation/Application	Performance Type	Standard
-----------------------	------------------	-----------------

Packaging Features	Packaging Method	Tube, Tube/Box
--------------------	------------------	-----------------------

Other	Additional Features	Short THT Pins
-------	---------------------	-----------------------

Product Compliance [Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

