



Search by Keyword or Part #

V23057A 2A101 Product Details



V23057A 2A101
(1393215-4)

TE Internal Number: 1393215-4

Active

Industrial Relays (General Purpose)

[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Relay Type = Power PCB Relay
- Relay Style = PCB
- Card E Series
- Contact Arrangement = 1 Form C, SPDT, 1 C/O
- Contact Current Rating = 5 A

[View all Features](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> ● None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> ● Power PCB Relay Card E (PDF, English) <p>Product Specifications:</p> <ul style="list-style-type: none"> ● None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> ● None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> ● None Available <p>CAD Files:</p> <ul style="list-style-type: none"> ● None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> ● Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> ● Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> ● Termination Type = Through Hole <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> ● Contact Current Rating (A) = 5 ● Coil Resistance (Ω) = 330 ● Coil Power, Nominal (mW) = 440 ● Actuating System = DC ● Coil Power, Nominal (W) = 0.44 ● Input Voltage (VDC) = 12 ● Dielectric Strength - Coil Contacts (V rms) = 4000 ● Tracking Resistance of Relay Base = PT1225 <p>Body Related Features:</p> <ul style="list-style-type: none"> ● Series = Card E ● Polarized = No ● Enclosure Color = Blue <p>Contact Related Features:</p> <ul style="list-style-type: none"> ● Relay Type = Power PCB Relay ● Mounting Options = PC Board ● Enclosure Type = Immersion Cleanable ● FCC Part 68 Isolation = No ● Contact Base Material = Silver Nickel 0.15 ● Approx. Dimensions (L x W x H) (mm [in]) = 28.0 x 25.0 x 10.8 [1.102 x .984 x .425] ● Contact Configuration = Single ● Pin Configuration = Industry Standard 2.5mm ● Wiring Diagram = 1 Form C ● Number of Poles = 1 	<p>Housing Related Features:</p> <ul style="list-style-type: none"> ● Version = Horizontal Version ● Pick-Up (V) = 8 ● Drop-Out (V) = 1.2 <p>Configuration Related Features:</p> <ul style="list-style-type: none"> ● Relay Style = PCB ● Contact Arrangement = 1 Form C, SPDT, 1 C/O ● Coil Magnetic System = Monostable ● Coil Suppression Diode = Without ● Coil Selection Criteria = Nominal Voltage ● Coil Latching = Without ● Status Indicator = None ● Number of Coils = 1 <p>Industry Standards:</p> <ul style="list-style-type: none"> ● RoHS/ELV Compliance = RoHS compliant, ELV compliant ● Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C ● RoHS/ELV Compliance History = Converted to comply with RoHS directive ● Approved Standards = VDE Component Mark, UL Recognized for Canada and US <p>Packaging Related Features:</p> <ul style="list-style-type: none"> ● Packaging Method = Tray <p>Other:</p> <ul style="list-style-type: none"> ● Electrical Spacing = 4.0mm Clearance 4.0mm Creepage ● Brand = Schrack



Corporate Information

- [Who We Are](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat with Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)

Sign up for our eNewsletter

Enter your email address

Follow Us On:

[Twitter](#) [Facet](#) [Flickr](#) [LinkedIn](#) [YouTube](#)

Visit Us On:

