



FORCE-GUIDED RELAYS



✓ Active

↓ 3D PDF

TE CONNECTIVITY (TE)

V23050-A1024-A533

Schrack | SR6-V23050 6 Pole Force Guided Relay

V23050A1024A533

TE Internal Number: 1415015-1

Alias ID: V23050-A1024-A533

[Converted to EU RoHS/ELV Compliant](#)

Contact Number of Poles **6**

Contact Arrangement **3 Form A (NO) + 1 Form B (NC)**

Coil Voltage Rating (VDC) **24**

Contact Current Rating (A) **8**

Contact Voltage Rating (VAC) **250**

CAD Files

[Customer View Model](#)

3D_STP.ZIP

English

[Customer View Model](#)

2D_DXF.ZIP

English

[3D PDF](#)

PDF

3D

[Customer View Model](#)

3D_IGS.ZIP

English

Catalog Pages/Data Sheets

[Safety Relay SR6](#)

PDF

English

Product Specifications

Product Specification

[Product Specification SR6](#)

PDF

English

[Definitions Relays](#)

PDF

English

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

Product Type

Relay

Relay Type

Force Guided Relay SR6 A/B/C/V

Electrical Characteristics

Coil Voltage Rating (VDC)

24

Contact Voltage Rating (VAC)	250
Coil Power Rating (DC) (mW)	1200
Contact Switching Voltage (Max) (VAC)	400
Contact Limiting Continuous Current (A)	8
Insulation Initial Dielectric Between Coil/Contact Class	3500 – 4000 V
Coil Current	50
Contact Switching Load (Min)	10mA @ 5V
Coil Power Rating Class (mW)	1 – 1.5 W
Insulation Creepage Between Contact and Coil	5.5 mm [.217 in]
Contact Limiting Breaking Current (A)	8
Coil Resistance (Ω)	480
Insulation Initial Dielectric Between Open Contacts (Vrms)	1500
Coil Magnetic System	Monostable, DC
Insulation Initial Dielectric Between Adjacent Contacts (Vrms)	3000
Insulation Initial Dielectric Between Contacts and Coil (Vrms)	4000
Insulation Creepage Class	3 – 5.5 mm
Contact Limiting Making Current (A)	8
Contact Limiting Short-Time Current (A)	8

Body Features	Weight	90 g [1.058 oz]
---------------	--------	--------------------------

Contact Features	Contact Number of Poles	6
	Contact Arrangement	3 Form A (NO) + 1 Form B (NC)
	Contact Current Rating (A)	8
	Contact Material	AgSnO2
	Terminal Type	PCB-THT
	Contact Special Features	Force Guided Contacts
	Contact Current Class	5 – 10 A

Mechanical Attachment	Mounting Type	Printed Circuit Board
-----------------------	---------------	------------------------------

Dimensions	Length	55 mm [2.167 in]
	Height	16.5 mm [.65 in]
	Insulation Clearance Between Contact and Coil	5.5 mm [.217 in]
	Insulation Clearance Class	5 – 8 mm
	Width Class (Mechanical)	14 – 20 mm

Width Class (Mechanical)	10 – 20 mm
Height Class (Mechanical)	16 – 20 mm
Width	16.51 mm [.65 in]
Length Class (Mechanical)	50 – 60 mm

Usage Conditions	Environmental Category of Protection	RTIII
	Environmental Ambient Temperature (Max)	70 °C [158 °F]
	Environmental Ambient Temperature Class	-25 – 70°C

Packaging Features	Packaging Method	Tube, Tube/Box
--------------------	------------------	-----------------------





Other	Comment	Well suited for emergency shut-off, machine control, elevator and escalator control, light barrier control
-------	---------	---

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>FORCE-GUIDED RELAYS</p>  <p>V23050-A1024-A542 V23050A1024A542</p> <p>Save to List</p> <p>Find Similar Products</p>	<p>HEAT SHRINK TUBING</p>  <p>SST-12-17/FR/97 SST-12-17/FR/97</p> <p>Save to List</p> <p>Find Similar Products</p>	<p>FORCE-GUIDED RELAYS</p>  <p>V23050-A1110-A542 V23050A1110A542</p> <p>Save to List</p> <p>Find Similar Products</p>	<p>PCB CONNECTOR KEYING</p>  <p>KEYING BLOCK 926495-1</p> <p>Save to List</p> <p>Find Similar Products</p>
---	--	---	--