



OJ-SS-124HM,000 Product Details

[Share](#) | [Print](#) | [Email](#)


Industrial Relays (General Purpose)

Always EU RoHS compliant but not ELV Compliant (Statement of Compliance)

Product Highlights:

- OJ/OJE Series
- Contact - Current Class = 5A to 10A Class, Less Than 16A
- Contact - Rated Current = 10 A
- Terminal Type = PCB-THT
- Contact - Arrangement = 1 Form A (NO)

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

OJ-SS-124HM,000 (1440007-2)

TE Internal Number: 1440007-2

Active

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [OJ-SS-HM SPEC,000 CUSTOMER DRAWING](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- [OJ-SS-124HM,000](#) (PDF, Japanese)

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Schematic](#)
- [Wiring Diagram](#)
- [PCB Layout \(Bottom Surface\)](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Electrical Characteristics:

- Contact - Current Class = 5A to 10A Class, Less Than 16A
- [Contact - Rated Current \(A\)](#) = 10
- Contact - Limiting Continuous Current (A) = 10
- Contact - Limiting Making Current (A) = 10
- Contact - Limiting Breaking Current (A) = 10
- Insulation - Initial Dielectric Between Coil/Contact Class = 3500V to 4000V Class
- Insulation - Initial Dielectric Between Open Contacts (V rms) = 750
- Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 4000
- Contact - Rated Voltage (VAC) = 277
- Contact - Rated Voltage (VDC) = 30
- Contact - Switching Voltage Max. (VAC) = 277
- Contact - Switching Voltage Max. (VDC) = 30
- Contact - Limiting Short-Time Current (A) = 10
- Contact - Switching Recommended Load, Min. = 100mA at 5V
- Coil - Rated Voltage (VDC) = 24
- [Coil - Resistance \(Ω\)](#) = 1280
- [Coil - Rated Power, DC \(mW\)](#) = 450
- Coil - Rated Power Class = 400mW to 500mW Class
- Insulation - Creepage Class = 5.5mm to 8mm Class
- Insulation - Clearance Class = 2.5mm to 4mm Class
- Insulation - Special Features = Tracking Index of Relay Base PTI250

Dimensions:

- Mechanical - Length Class = 16mm to 20mm Class
- Length (mm [in]) = 18.20 [0.717]
- Mechanical - Width Class = 10mm to 12mm Class
- Width (mm [in]) = 10.20 [0.400]

Body Features:

- Mount Type = PCB
- Weight (g [oz]) = 9.00 [0.318]

Contact Features:

- Terminal Type = PCB-THT
- Contact Material = Ag
- Contact - Number of Poles = 1

Configuration Features:

- [Contact - Arrangement](#) = 1 Form A (NO)
- [Coil - Magnetic System](#) = Monostable, DC
- Coil - Special Features = UL Coil Insulation Class B

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS/Not ELV Compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS not ELV compliant
- Approved/Registered Standards = VDE, cULus, TUEV, CQC

Environmental:

- Environmental - Category of Protection = RTII
- Environmental - Ambient Temperature, Max. (°C [°F]) = 70 [158]
- Environmental - Ambient Temperature Class = 50°C to 70°C Class

Packaging Features:

- Packaging Method = Tray

Other:

- Series = OJ/OJE

Feedback

- Mechanical - Height Class = 14mm to 15mm Class
- Height (mm [in]) = 14.70 [0.579]
- Insulation - Clearance Between Contact and Coil (mm [in]) = 3.2 [0.126]
- Insulation - Creepage Between Contact and Coil (mm [in]) = 6.4 [0.252]

- Brand = OEG

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)
- [AODA Multi-Year Accessibility Plan](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed

