## 1461400-1 Product Details



1461400-1 Active

#### Mid-Range PC Board Relays



#### **Product Highlights:**

- OJE Series
- Contact Arrangement = 1 Form A, SPST-NO, 1 N/O
- Contact Current Rating = 5 Amps.
- Monostable Coil Magnetic System
- Without Coil Suppression Diode

View all Features | Find Similar Products

# Previous [1] 2 3 4 5 ... 20 Next Quick Links

- Check Pricing & Availability
  - Search for Tooling
- Product Feature Selector
- Compare Products
- Contact Us About This Product

#### **Documentation & Additional Information**

#### **Product Drawings:**

• OJ-SH-DM SPEC,000 CUSTOMER DRAWING (PDF, English)

#### Catalog Pages/Data Sheets:

None Available

#### **Product Specifications:**

None Available

#### **Application Specifications:**

None Available

#### **Instruction Sheets:**

None Available

#### **CAD Files:**

None Available

#### **Additional Information:**

Product Line Information

#### **Additional Product Images:**

- Schematic
- Wiring Diagram
- PCB Layout (Bottom Surface)

#### Related Products:

• <u>Tooling</u>

## List all Documents

Product Features (Please use the Product Drawing for all design activity)

## **Product Type Features:**

• <u>Termination Type</u> = Through Hole

## **Electrical Characteristics:**

- Contact Current Rating (Amps.) = 5
- Coil Resistance (?) = 55
- <u>Coil Power, Nominal (mW)</u> = 450
- Actuating System = DC
- <u>Input Voltage (VDC)</u> = 5

## **Body Related Features:**

- <u>Series</u> = OJE
- Polarized = No

#### **Contact Related Features:**

- Mounting Options = PC Board
- Enclosure = Sealed
- FCC Part 68 Isolation = No
- Relay Type = PCB
- <u>Contact Material</u> = Silver Cadmium Oxide
- Approx. Dimensions (L x W x H) (mm[in]) = 18.20 x 10.20 x 14.70 [.717 x .402 x .580]
- Approved Standards = UL Recognized, CSA Certified, TUV Approved, VDE Component Mark

## Configuration Related Features:

- Contact Arrangement = 1 Form A, SPST-NO, 1 N/O
- <u>Coil Magnetic System</u> = Monostable
- <u>Coil Suppression Diode</u> = Without
- <u>Coil Selection Criteria</u> = Nominal Voltage
- Coil Latching = Without
- <u>LED Indicator</u> = Without

## Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240C, Wave solder capable to 260C, Wave solder capable to 265C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

## Packaging Related Features:

• Dielectric Between Coil and Contacts (kV) = 3

#### Other

● Brand = OEG