
# 1461403-4 Product Details



Active

## Mid-Range PC Board Relays

Always EU RoHS compliant but not ELV Compliant (Statement of Compliance)



## **Documentation & Additional Information**



• OJE-SH-LMH SPEC.000 CUSTOMER DRAWING (PDF, English)

## Catalog Pages/Data Sheets:

None Available

## **Product Specifications:**

None Available

## **Application Specifications:**

None Available

## Instruction Sheets:

None Available

## CAD Files:

None Available

## Additional Information:

- Schematic

• <u>Tooling</u>

## List all Documents

Product Features (Please use the Product Drawing for all design activity)

## **Product Type Features:**

• <u>Termination Type</u> = Through Hole

## **Electrical Characteristics:**

- <u>Contact Current Rating (Amps.)</u> = 8
- Coil Resistance (?) = 720
- ٠ Coil Power, Nominal (mW) = 200
- Actuating System=DC
- Input Voltage (VDC) = 12 ٠

## **Body Related Features:**

- <u>Series</u> = OJE
- Polarized = No

## **Contact Related Features:**

- <u>Mounting Options</u> = PC Board
- Enclosure = Sealed
- FCC Part 68 Isolation = No
- Relay Type = PCB
- Contact Material = Silver Cadmium Oxide
- Approx. Dimensions (L x W x H) (mm [in]) = 18.20 x 10.20 x 14.70 [.717 x .402 x .580]
- Approved Standards = UL Recognized, CSA Certified, TUV Approved, VDE Component Mark

Provide Website Feedback | Contact Customer Support Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support 2008 Tyco Electronics Corporation All Rights Reserved

## **Configuration Related Features:**

- ٠ Contact Arrangement = 1 Form A, SPST-NO, 1 N/O
- Coil Magnetic System = Monostable
- Coil Suppression Diode = Without
- Coil Selection Criteria = Nominal Voltage
- Coil Latching = Without
- LED Indicator = Without

## **Industry Standards:**

- <u>RoHS/ELV Compliance</u> = RoHS/Not ELV Compliant
- Lead Free Solder Processes = Wave solder capable to 240C, Wave solder • capable to 260C, Wave solder capable to 265C
- ٠ RoHS/ELV Compliance History = Always was RoHS not ELV compliant

## Packaging Related Features:

• Dielectric Between Coil and Contacts (kV) = 3

## Other:

٠ Brand = OEG

 Product Line Information Additional Product Images:

- Wiring Diagram •
- ٠ PCB Layout (Bottom Surface)

**Related Products:** 



- Check Pricing & Availability •
- Search for Tooling Product Feature Selector •
- Compare Products
- Contact Us About This Product