



RELAYS, CONTACTORS & SWITCHES

## SIGNAL RELAYS



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### IM01CGR=140MW 3V HDV

Axicom | IM

1462038-4

TE Internal Number: 1462038-4

Always EU RoHS/ELV Compliant

Contact Voltage Rating **250 VAC [ 220 VDC ]**

Coil Power Rating (DC) (mW) **140**

Isolation (HF Parameter) **-37dB @ 100MHz, -18.8dB @ 900MHz**

Insertion Loss (HF Parameter) **-.33dB @ 900MHz, -.03dB @ 100MHz**

Insulation Initial Resistance (MΩ) **1000000**



### Product Drawings

**IM2-G-Relay**

PDF  
English

**IM-Relay Marking**

PDF  
English

### CAD Files

**Customer View Model**

2D\_DXF.ZIP  
English

**3D PDF**

PDF  
3D

**Customer View Model**

3D\_IGS.ZIP  
English

**Customer View Model**

3D\_STP.ZIP  
English

### Product Specifications

Product Specification

**IM Relay Datasheet**

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Relay
	Relay Type	IM Relay
Electrical Characteristics	Contact Voltage Rating	<b>250 VAC [ 220 VDC ]</b>
	Coil Power Rating (DC) (mW)	<b>140</b>
	Insulation Initial Resistance (M $\Omega$ )	<b>1000000</b>
	Coil Voltage Rating (VAC)	<b>3</b>
	Contact Switching Voltage (Max)	<b>250 VAC [ 220 VDC ]</b>
	Coil Magnetic System	<b>Monostable, DC</b>
	Insulation Initial Dielectric Between Coil/Contact Class	<b>1500 V – 2500 VA</b>
	Insulation Initial Dielectric Between Adjacent Contacts (Vrms)	<b>1800</b>
	Insulation Initial Dielectric Between Contacts and Coil (Vrms)	<b>1800</b>
	Contact Limiting Making Current (A)	<b>2</b>
	Insulation Initial Dielectric Between Open Contacts (Vrms)	<b>1500</b>
	Actuating System	<b>DC</b>
	Contact Limiting Short-Time Current (A)	<b>2</b>
	Contact Limiting Continuous Current (A)	<b>2</b>
	Coil Resistance ( $\Omega$ )	<b>64</b>
	Contact Switching Load (Min)	<b>.1mA @ .0001V</b>
	Contact Limiting Breaking Current (A)	<b>2</b>
	Coil Power Rating Class	<b>50 – 300mW</b>
	Coil Type	<b>Monostable</b>
	Voltage Standing Wave Ration (HF Parameter)	<b>1.07 @ 100MHz, 1.45 @ 900MHz</b>
Signal Characteristics	Isolation (HF Parameter)	<b>-37dB @ 100MHz, -18.8dB @ 900MHz</b>
	Insertion Loss (HF Parameter)	<b>-.33dB @ 900MHz, -.03dB @ 100MHz</b>
Body Features	Insulation Special Features	<b>2500V Initial Surge Withstand Voltage between Contacts &amp; Coil</b>

Weight (oz) **.75**

---

Contact Features	Terminal Type	<b>PCB-SMT</b>
	Contact Current Rating (A)	<b>2</b>
	Contact Arrangement	<b>2 Form C (CO)</b>
	Contact Material	<b>PdRu</b>
	Contact Number of Poles	<b>2</b>
	Contact Special Features	<b>Bifurcated/Twin Contacts</b>
	Contact Current Class	<b>0 – 2 A</b>
	Contact Plating Material	<b>Gold</b>

---

Mechanical Attachment	Mounting Type	<b>Printed Circuit Board</b>
-----------------------	---------------	------------------------------

---

Dimensions	Length Class (Mechanical)	<b>0 – 10 mm</b>
	Width Class (Mechanical)	<b>0 – 6 mm</b>
	Length (in)	<b>10</b>
	Width	<b>6 mm [ .236 in ]</b>
	Height Class (Mechanical)	<b>0 – 6 mm</b>
	Dimensions (L x W x H) (Approximate)	<b>10 x 6 x 5.65 mm [ .393 x .236 x .222 in ]</b>
	Height	<b>5.6 mm [ .221 in ]</b>

---

Usage Conditions	Environmental Category of Protection	<b>RTV</b>
	Environmental Ambient Temperature (Max)	<b>85 °C [ 85 °F ]</b>
	Environmental Ambient Temperature Class	<b>70 – 85°C</b>

---

Operation/Application	Performance Type	<b>High Dielectric</b>
-----------------------	------------------	------------------------

---

Packaging Features	Packaging Method	<b>Reel</b>
--------------------	------------------	-------------

---

Other	Additional Features	<b>Gull Wing</b>
-------	---------------------	------------------

---

Product Compliance [Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

