


Corporate Home | [Electronic Components](#) | [Segments](#) | [Who We Are](#)


Worldwide



Our commitment. Your advantage.

[Products](#) | [Documentation](#) | [Resources](#) | [My Account](#) | [Customer Support](#)

V23061B1007A401 Product Details



V23061B1007A401

(2-1393223-1)

TE Internal Number: 2-1393223-1

Active

View 3D PDF

Industrial Relays (General Purpose)

Converted to EU RoHS but not ELV Compliant

(Statement of Compliance)

Product Highlights:

- MSR Series
- Contact Arrangement = 1 Form C, SPDT, 1 C/O
- Contact Current Rating = 8 Amps.
- Monostable Coil Magnetic System
- Without Coil Suppression Diode

[View all Features](#)

Quick Links

- Check Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [Miniature Power PCB Relay MSR](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: [\(CAD Format & Compression Information\)](#)

- [2D Drawing](#) (DXF, Version 0GH1)
- [3D Model](#) (IGES, Version 0GH1)
- [3D Model](#) (STEP, Version 0GH1)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Termination Type](#) = Through Hole

Electrical Characteristics:

- [Contact Current Rating \(Amps.\)](#) = 8
- [Coil Resistance \(Ω\)](#) = 2270
- [Coil Power, Nominal \(mW\)](#) = 220
- [Actuating System](#) = DC
- [Coil Power, Nominal \(W\)](#) = 0.22
- [Input Voltage \(VDC\)](#) = 24
- Dielectric Strength - Coil Contacts (V rms) = 4000
- Coil Rating = Sensitive

Body Related Features:

- [Series](#) = MSR
- Polarized = No
- Enclosure Color = White

Contact Related Features:

- [Mounting Options](#) = PC Board, Socket
- [Enclosure](#) = Immersion Cleanable
- FCC Part 68 Isolation = No
- Relay Type = PCB
- [Contact Base Material](#) = Silver Cadmium Oxide
- Approx. Dimensions (L x W x H) (mm [in]) = 30.00 x 10.00 x 15.00 [1.182 x .394 x .591]
- Contact Type = Single
- Pin Configuration = Industry Standard 3.2mm
- Wiring Diagram = 1 Form C
- Approved Standards = VDE Component Mark, UL Recognized for Canada and US
- Number of Poles = 1

Housing Related Features:

- Version = Pinning 3.2mm, Version for IEC 60335-1 (domestic appliances)
- Pick-Up (V) = 16.8
- Drop-Out (V) = 2.4

Configuration Related Features:

- [Contact Arrangement](#) = 1 Form C, SPDT, 1 C/O
- [Coil Magnetic System](#) = Monostable
- [Coil Suppression Diode](#) = Without
- [Coil Selection Criteria](#) = Nominal Voltage
- Coil Latching = Without
- Status Indicator = None
- Number of Coils = 1

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS/Not ELV Compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C
- RoHS/ELV Compliance History = Converted to comply with RoHS not ELV directives
- Coil Insulation Classification = UL Class A


Packaging Related Features:

- Packaging Method = Plastic Bar

Other:

- Electrical Spacing = 8.0mm Clearance 8.0mm Creepage
- Brand = Schrack

BOOKMARK



Provide Website Feedback | [Need Help?](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2009 Tyco Electronics Corporation All Rights Reserved

http://www.tycoelectronics.com/catalog/bin/TE.Connect?C=1&M=BYPN&TCPN=2-1393223-1&RQPN=2-1393223-1

7/30/2009