



## RT33L024 Product Details

[Share](#) | [Print](#) | [Email](#)


**RT33L024**  
(3-1393240-5)

TE Internal Number: 3-1393240-5

Active

### Industrial Relays (General Purpose)

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

#### Product Highlights:

- RT1 Inrush Series
- Contact - Current Class = 10A to 20A Class, Greater Than 16A
- Contact - Rated Current = 16 A
- Terminal Type = PCB-THT, Plug-in
- Contact - Arrangement = 1 Form A (NO)

[View all Features](#)

### Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Power PCB Relay RT1 Inrush</a> (PDF, English)</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Line Information</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul>

[List all Documents](#)

Feedback

## Product Features (Please use the Product Drawing for all design activity)

<p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>• Contact - Current Class = 10A to 20A Class, Greater Than 16A</li> <li>• <a href="#">Contact - Rated Current (A)</a> = 16</li> <li>• Contact - Limiting Continuous Current (A) = 16</li> <li>• Contact - Limiting Making Current (A) = 80</li> <li>• Contact - Limiting Breaking Current (A) = 16</li> <li>• Insulation - Initial Dielectric Between Coil/Contact Class = &gt;4000V Class</li> <li>• Insulation - Initial Dielectric Between Open Contacts (V rms) = 1000</li> <li>• Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 5000</li> <li>• Contact - Rated Voltage (VAC) = 250</li> <li>• Contact - Switching Voltage Max. (VAC) = 400</li> <li>• Contact - Limiting Short-Time Current (A) = 16</li> <li>• Coil - Rated Voltage (VDC) = 24</li> <li>• <a href="#">Coil - Resistance (Ω)</a> = 1440</li> <li>• <a href="#">Coil - Rated Power, DC (mW)</a> = 400</li> <li>• Coil - Rated Power Class = 300mW to 400mW Class</li> <li>• Insulation - Creepage Class = &gt;8mm Class</li> <li>• Insulation - Clearance Class = &gt;8mm Class</li> <li>• Insulation - Special Features = Tracking Index of Relay Base PTI250</li> </ul> <p><b>Dimensions:</b></p> <ul style="list-style-type: none"> <li>• Mechanical - Length Class = 25mm to 30mm Class</li> <li>• Length (mm [in]) = 29.00 [1.142]</li> <li>• Mechanical - Width Class = 12mm to 16mm Class</li> <li>• Width (mm [in]) = 12.70 [0.500]</li> <li>• Mechanical - Height Class = 15mm to 16mm Class</li> <li>• Height (mm [in]) = 15.70 [0.618]</li> <li>• Insulation - Clearance Between Contact and Coil (mm [in]) = 10 [0.394]</li> </ul>	<p><b>Body Features:</b></p> <ul style="list-style-type: none"> <li>• Mount Type = PCB, Socket</li> <li>• Weight (g [oz]) = 14.00 [0.494]</li> </ul> <p><b>Contact Features:</b></p> <ul style="list-style-type: none"> <li>• Terminal Type = PCB-THT, Plug-in</li> <li>• Contact Material = AgSnO</li> <li>• Contact - Number of Poles = 1</li> </ul> <p><b>Configuration Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Contact - Arrangement</a> = 1 Form A (NO)</li> <li>• <a href="#">Coil - Magnetic System</a> = Monostable, DC</li> <li>• Coil - Special Features = UL Coil Insulation Class F</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">RoHS/ELV Compliance</a> = RoHS compliant, ELV compliant</li> <li>• <a href="#">Lead Free Solder Processes</a> = Wave solder capable to 260°C, Wave solder capable to 240°C, Wave solder capable to 265°C</li> <li>• RoHS/ELV Compliance History = Converted to comply with RoHS directive</li> <li>• Approved/Registered Standards = cCSAus, cULus, VDE</li> </ul> <p><b>Environmental:</b></p> <ul style="list-style-type: none"> <li>• Environmental - Category of Protection = RTII</li> <li>• Environmental - Ambient Temperature, Max. (°C [°F]) = 85 [185]</li> <li>• Environmental - Ambient Temperature Class = 70°C to 85°C Class</li> </ul> <p><b>Packaging Features:</b></p> <ul style="list-style-type: none"> <li>• Packaging Method = Tube</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• Series = RT1 Inrush</li> </ul>
---	---

- Insulation - Creepage Between Contact and Coil (mm [in]) = 10 [0.394]

- Brand = Schrack
- Accessories/Socket Type = DIN-rail Socket, PCB Socket

#### Corporate Information

[About TE](#)  
[Investors](#)  
[News Room](#)  
[Supplier Portal](#)  
[Careers](#)  
[Terms & Conditions](#)  
[Privacy Policy](#)  
[AODA Accessibility Policy](#)  
[AODA Multi-Year Accessibility Plan](#)

#### Quick Links

[Distributor Inventory](#)  
[Product Cross Reference](#)  
[Documents & Drawings](#)  
[Product Compliance Support Center](#)  
[Site Map](#)

#### Customer Support

[Email or Chat With Us](#)  
[Find a Phone Number](#)  
[Knowledge Base](#)  
[Manage Your Account](#)

#### Keep Me Informed

