Skip to content	
<u> </u>	
<i>T</i>yco Electronics	
Our commitment. Your advantage.	

• Products

×

O By Type

- Connectors
 - Electromechanical Components
 - Electronic Modules
 - Fiber Optics
 - <u>Filters</u>
 - Identification & Labeling
 - Passive Components
 - Power Sources
 - RF & Microwave Products
 - Tooling Products Touch Screen Displays
 - Tubing, Molded and Harnessing Products
 - Wire, Cable and Cable Assemblies
 - List all product types...
- O By Industry
 - Aerospace & Defense Products
 - Appliance
 - Automotive
 - Communications
 - Computer & Consumer Electronics Industrial & Commercial
 - Instrumentation & Medical
- O By Brand
- 0 <u>A to Z</u>
- O <u>Product News</u>

Documentation

- O Find Documents & Drawings
- Find CAD Models 0
- O <u>SPICE/Electrical Models</u>
- O NAFTA Certificate of Origin
- O White Papers

• <u>Resources</u>

- O RoHS Compliance & Alternates
- O <u>Cross Reference Products</u>
- O Compare Multiple Products
- O Check Distributor Inventory
- O Find Authorized Distributors

• My Account

- O <u>Sign In</u>
- O Register

<u>Customer Support</u>

- O <u>Support</u>
- O RoHS Support Center

O Glossary of Terms

eBulletin Newsletter 0

OJE-SS-112LM,000 Product Details



OJE-SS-112LM,000

Active

Mid-Range PC Board Relays



Documentation & Additional Information

Product Drawings:

• OJE-SS-LM SPEC,000 CUSTOMER DRAWING (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

• <u>Termination Type</u> = Through Hole

Electrical Characteristics:

- Contact Current Rating (Amps.) = 3
- <u>Coil Resistance (?)</u> = 720
- Coil Power, Nominal (mW) = 200
- Actuating System=DC
- Input Voltage (VDC) = 12

Body Related Features:

- Series = OJEPolarized = No

Contact Related Features:

- Mounting Options = PC Board
- Enclosure = Flux-Tight
- FCC Part 68 Isolation = No
- Relay Type = PCB
- <u>Contact Material</u> = Silver Cadmium Oxide
- Approx. Dimensions (L x W x H) (mm[in]) = 18.20 x 10.20 x 14.70 [.717 x 402 x 5801
- Approved Standards = UL Recognized, CSA Certified, VDE Component . Mark, TUV Approved

Configuration Related Features:

- Contact Arrangement = 1 Form A, SPST-NO, 1 N/O
- Coil Magnetic System = Monostable •
- <u>Coil Suppression Diode</u> = Without
- Coil Selection Criteria = Nominal Voltage •
- Coil Latching = Without •
- <u>LED Indicator</u> = Without

Industry Standards:

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240C, Wave solder capable to 260C, Wave solder capable to 265C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Packaging Related Features:

• Dielectric Between Coil and Contacts (kV) = 3

Other:

٠ Brand = OEG

Previous 1 ... 6 7 [8] 9 10 ... 20 Next Quick Links

- Check Pricing & Availability
- Search for Tooling
- Product Feature Selector Compare Products
- Contact Us About This Product

Additional Information:

Product Line Information

Additional Product Images:

- Schematic

- - - Wiring Diagram
 - PCB Layout (Bottom Surface)

Related Products:

• <u>Tooling</u>

View all Features | Find Similar Products

Provide Website Feedback | Contact Customer Support Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support 2008 Tyco Electronics Corporation All Rights Reserved