



# RTD14-012 Product Details

[Share](#) | [Print](#) | [Email](#)


**RTD14-012**  
(6-1393238-2)

TE Internal Number: 6-1393238-2

Active

View 3D PDF

## Industrial Relays (General Purpose)

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

### Product Highlights:

- RT1 Series
- Contact - Current Class = 10A to 20A Class, Greater Than 16A
- Contact - Rated Current = 16 A
- Terminal Type = PCB-THT, Plug-in
- Contact - Arrangement = 1 Form C (CO)

[View all Features](#)

### Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

## Documentation & Additional Information

**Product Drawings:**

- None Available

**Catalog Pages/Data Sheets:**

- [Power PCB Relay RT1](#) (PDF, English)

**Product Specifications:**

- None Available

**Application Specifications:**

- None Available

**Instruction Sheets:**

- None Available

**CAD Files: (CAD Format & Compression Information)**

- [2D Drawing](#) (DXF, Version C)
- [3D Model](#) (IGES, Version C)
- [3D Model](#) (STEP, Version C)

[List all Documents](#)

**Additional Information:**

- [Product Line Information](#)

**Related Products:**

- [Tooling](#)

Feedback

## Product Features (Please use the Product Drawing for all design activity)

**Electrical Characteristics:**

- Contact - Current Class = 10A to 20A Class, Greater Than 16A
- [Contact - Rated Current \(A\)](#) = 16
- Contact - Limiting Continuous Current (A) = 16
- Contact - Limiting Making Current (A) = 30
- Contact - Limiting Breaking Current (A) = 16
- Insulation - Initial Dielectric Between Coil/Contact Class = >4000V Class
- Insulation - Initial Dielectric Between Open Contacts (V rms) = 1000
- Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 5000
- Contact - Rated Voltage (VAC) = 250
- Contact - Switching Voltage Max. (VAC) = 400
- Contact - Limiting Short-Time Current (A) = 16
- Coil - Rated Voltage (VDC) = 12
- [Coil - Resistance \(Ω\)](#) = 360
- [Coil - Rated Power, DC \(mW\)](#) = 400
- Coil - Rated Power Class = 300mW to 400mW Class
- Insulation - Creepage Class = >8mm Class
- Insulation - Clearance Class = >8mm Class
- Insulation - Special Features = Tracking Index of Relay Base PTI250

**Dimensions:**

- Mechanical - Length Class = 25mm to 30mm Class
- Length (mm [in]) = 29.00 [1.142]
- Mechanical - Width Class = 12mm to 16mm Class
- Width (mm [in]) = 12.70 [0.500]
- Mechanical - Height Class = 15mm to 16mm Class
- Height (mm [in]) = 15.70 [0.618]

**Body Features:**

- Mount Type = PCB, Socket
- Weight (g [oz]) = 14.00 [0.494]

**Contact Features:**

- Terminal Type = PCB-THT, Plug-in
- Contact Material = AgNi90/10
- Contact - Number of Poles = 1

**Configuration Features:**

- [Contact - Arrangement](#) = 1 Form C (CO)
- [Coil - Magnetic System](#) = Monostable, DC
- Coil - Special Features = UL Coil Insulation Class F

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 260°C, Wave solder capable to 240°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive
- Approved/Registered Standards = cULus, cCSAus, VDE

**Environmental:**

- Environmental - Category of Protection = RTIII
- Environmental - Ambient Temperature, Max. (°C [°F]) = 85 [185]
- Environmental - Ambient Temperature Class = 70°C to 85°C Class

**Packaging Features:**

- Packaging Method = Tube

- Insulation - Clearance Between Contact and Coil (mm [in]) = 10 [0.394]
- Insulation - Creepage Between Contact and Coil (mm [in]) = 10 [0.394]

**Other:**

- Series = RT1
- Brand = Schrack
- Accessories/Socket Type = PCB Socket, DIN-rail Socket

**Corporate Information**

[About TE](#)  
[Investors](#)  
[News Room](#)  
[Supplier Portal](#)  
[Careers](#)  
[Terms & Conditions](#)  
[Privacy Policy](#)  
[AODA Accessibility Policy](#)  
[AODA Multi-Year Accessibility Plan](#)

**Quick Links**

[Distributor Inventory](#)  
[Product Cross Reference](#)  
[Documents & Drawings](#)  
[Product Compliance Support Center](#)  
[Site Map](#)

**Customer Support**

[Email or Chat With Us](#)  
[Find a Phone Number](#)  
[Knowledge Base](#)  
[Manage Your Account](#)

**Keep Me Informed**