



KUMP-11D18-24 Product Details

[Share](#) | [Print](#) | [Email](#)


KUMP-11D18-24
(7-1393116-2)

TE Internal Number: 7-1393116-2

Active

Industrial Relays (General Purpose)

Converted to EU RoHS but not ELV Compliant (Find RoHS Compliant Alternates/Statement of Compliance)

Product Highlights:

- KUMP Series
- Contact - Current Class = 10A to 20A Class, Less Than 16A
- Contact - Rated Current = 15 A
- Terminal Type = Quick Connect, Solder
- Contact - Arrangement = 2 Form C (CO)

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Schematic](#)
- [Wiring Diagram](#)
- [Front View](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Electrical Characteristics:

- Contact - Current Class = 10A to 20A Class, Less Than 16A
- [Contact - Rated Current \(A\)](#) = 15
- Contact - Limiting Continuous Current (A) = 15
- Contact - Limiting Making Current (A) = 15
- Contact - Limiting Breaking Current (A) = 15
- Insulation - Initial Dielectric Between Coil/Contact Class = 1500V to 2500VA Class
- Insulation - Initial Dielectric Between Open Contacts (V rms) = 1200
- Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 2200
- Contact - Rated Voltage (VAC) = 277
- Contact - Limiting Short-Time Current (A) = 15
- Contact - Switching Recommended Load, Min. = 300mA at 12V
- Coil - Rated Voltage (VDC) = 24
- [Coil - Resistance \(Ω\)](#) = 472
- [Coil - Rated Power, DC \(mW\)](#) = 1250
- Coil - Rated Power Class = 1W to 1.5W Class
- Insulation - Initial Dielectric Between Adjacent Contacts (V rms) = 2200
- Insulation - Initial Insulation Resistance (MΩ) = 100000

Dimensions:

- Mechanical - Length Class = 35mm to 40mm Class
- Length (mm [in]) = 38.90 [1.550]
- Mechanical - Width Class = 30mm to 40mm Class
- Width (mm [in]) = 35.70 [1.405]
- Mechanical - Height Class = 40mm to 50mm Class
- Height (mm [in]) = 50.00 [1.970]

Body Features:

- Mount Type = Socket
- Weight (g [oz]) = 85.00 [2.988]

Contact Features:

- Terminal Type = Quick Connect, Solder
- Contact Material = AgCdO
- Contact - Number of Poles = 2

Configuration Features:

- [Contact - Arrangement](#) = 2 Form C (CO)
- [Coil - Magnetic System](#) = Monostable, DC
- Coil - Special Features = UL Coil Insulation Class B

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS/Not ELV Compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Converted to comply with RoHS not ELV directives
- Approved/Registered Standards = CSA, UL

Environmental:

- Environmental - Category of Protection = RTI
- Environmental - Ambient Temperature, Max. (°C [°F]) = 70 [158]
- Environmental - Ambient Temperature Class = 50°C to 70°C Class

Packaging Features:

- Packaging Method = Tray

Other:

- [Series](#) = KUMP
- Brand = Potter & Brumfield
- Accessories/Socket Type = DIN-rail Socket, PCB Socket, Snap-in Socket, Track mount Socket, Chassis mount Socket

Feedback

