




MID-RANGE



✓ Active

↓ **PRODUCT DRAWING**
English

TE CONNECTIVITY (TE)

FCB-405-0621M=M83536/6-021M

CII | FCB 5-10 Amp Relay

FCB-405-0621M

TE Internal Number: 8-1617760-1

Mil-Spec: M83536/6-021M

[Not EU RoHS or ELV Compliant](#)

[Find Compliant Alternatives](#)

Contact Arrangement **4 Form C, 4PDT, 4 C/O**

Coil Suppression Diode **With**

Auxiliary Contacts **Without**

Terminal Plating **Tin-Lead**

Contact Current Rating (A) **5**

Product Drawings

[FCB-405-0621M=M83536/6-021M](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type

Relay

Relay Type

Military/Aerospace Mid-Range

Enclosure Type

Hermetically Sealed

Terminal Configuration

Solder Hook

Electrical Characteristics

Coil Suppression Diode

With

Coil Voltage Rating (VDC)

28

Coil Resistance (Ω)

400

Back EMF Suppression

With

Coil Magnetic System

Polarized, Monostable

Vibration

30G's, 70 – 3000Hz

Shock

200G's, 6ms

Actuating System

DC

Contact Features

Contact Arrangement

4 Form C, 4PDT, 4 C/O

Auxiliary Contacts	Without
Terminal Plating	Tin-Lead
Contact Current Rating (A)	5
Contact Base Material	Silver Cadmium Oxide

Mechanical Attachment	Mounting Type	Raised Vertical Flange Mount
-----------------------	---------------	-------------------------------------

Usage Conditions	Operating Temperature Range (°C)	-70 – 125
------------------	----------------------------------	------------------

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)