



# RT314012 Product Details

[Share](#) | [Print](#) | [Email](#)


## Industrial Relays (General Purpose)

[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

### Product Highlights:

- RT1 Series
- Contact - Current Class = 10A to 20A Class, Greater Than 16A
- Contact - Rated Current = 16 A
- Terminal Type = PCB-THT, Plug-in
- Contact - Arrangement = 1 Form C (CO)

[View all Features](#)

### Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

**RT314012**  
(9-1393239-5)

TE Internal Number: 9-1393239-5

**Active**

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

## Documentation & Additional Information

Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.

### Additional Information:

- [Product Line Information](#)

### Related Products:

- [Tooling](#)

## Product Features (Please use the Product Drawing for all design activity)

### Electrical Characteristics:

- Contact - Current Class = 10A to 20A Class, Greater Than 16A
- [Contact - Rated Current \(A\)](#) = 16
- Contact - Limiting Continuous Current (A) = 16
- Contact - Limiting Making Current (A) = 30
- Contact - Limiting Breaking Current (A) = 16
- Insulation - Initial Dielectric Between Coil/Contact Class = >4000V Class
- Insulation - Initial Dielectric Between Open Contacts (V rms) = 1000
- Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 5000
- Contact - Rated Voltage (VAC) = 250
- Contact - Switching Voltage Max. (VAC) = 400
- Contact - Limiting Short-Time Current (A) = 16
- Coil - Rated Voltage (VDC) = 12
- [Coil - Resistance \(Ω\)](#) = 360
- [Coil - Rated Power, DC \(mW\)](#) = 400
- Coil - Rated Power Class = 300mW to 400mW Class
- Insulation - Creepage Class = >8mm Class
- Insulation - Clearance Class = >8mm Class
- Insulation - Special Features = Tracking Index of Relay Base PTI250

### Dimensions:

- Mechanical - Length Class = 25mm to 30mm Class
- Length (mm [in]) = 29.00 [1.142]
- Mechanical - Width Class = 12mm to 16mm Class
- Width (mm [in]) = 12.70 [0.500]
- Mechanical - Height Class = 15mm to 16mm Class
- Height (mm [in]) = 15.70 [0.618]
- Insulation - Clearance Between Contact and Coil (mm [in]) = 10 [0.394]
- Insulation - Creepage Between Contact and Coil (mm [in]) = 10 [0.394]

### Body Features:

- Mount Type = PCB, Socket
- Weight (g [oz]) = 14.00 [0.494]

### Contact Features:

- Terminal Type = PCB-THT, Plug-in
- Contact Material = AgNi90/10
- Contact - Number of Poles = 1

### Configuration Features:

- [Contact - Arrangement](#) = 1 Form C (CO)
- [Coil - Magnetic System](#) = Monostable, DC
- Coil - Special Features = UL Coil Insulation Class F

### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive
- Approved/Registered Standards = cULus, cCSAus, VDE

### Environmental:

- Environmental - Category of Protection = RTII
- Environmental - Ambient Temperature, Max. (°C [°F]) = 85 [185]
- Environmental - Ambient Temperature Class = 70°C to 85°C Class

### Packaging Features:

- Packaging Method = Tube

### Other:

- [Series](#) = RT1
- Brand = Schrack
- Accessories/Socket Type = PCB Socket, DIN-rail Socket

Feedback

## Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

## Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

## Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

## Keep Me Informed



[Terms & Conditions](#)

[Privacy Policy](#)

[AODA Accessibility Policy](#)

[AODA Multi-Year Accessibility  
Plan](#)