



SIGNAL RELAYS



✓ Active

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**

TE CONNECTIVITY (TE)

IM06CGR=140MW12V HDV

[Axicom](#) | [IM](#)

9-1462037-9

TE Internal Number: 9-1462037-9

[Always EU RoHS/ELV Compliant](#)

Contact Voltage Rating **250 VAC [220 VDC]**

Coil Power Rating (DC) (mW) **140**

Isolation (HF Parameter) **-37dB @ 100MHz, -18.8dB @ 900MHz**

Insertion Loss (HF Parameter) **-.33dB @ 900MHz, -.03dB @ 100MHz**

Insulation Initial Resistance (MΩ) **1000000**

Product Drawings

[IM2-G-Relay](#)

PDF
English

[IM-Relay Marking](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Product Specifications

Product Specification

[IM Relay Datasheet](#)

PDF
English

[Definitions Relays](#)

PDF
English


Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	Relay Type	IM Relay
Electrical Characteristics	Contact Voltage Rating	250 VAC [220 VDC]
	Coil Power Rating (DC) (mW)	140
	Insulation Initial Resistance (MΩ)	1000000
	Coil Voltage Rating (VAC)	12
	Contact Switching Voltage (Max)	250 VAC [220 VDC]
	Coil Magnetic System	Monostable, DC
	Insulation Initial Dielectric Between Coil/Contact Class	1500 V – 2500 VA
	Insulation Initial Dielectric Between Adjacent Contacts (Vrms)	1800
	Insulation Initial Dielectric Between Contacts and Coil (Vrms)	1800
	Contact Limiting Making Current (A)	2
	Insulation Initial Dielectric Between Open Contacts (Vrms)	1500
	Actuating System	DC
	Contact Limiting Short-Time Current (A)	2
	Contact Limiting Continuous Current (A)	2
	Coil Resistance (Ω)	1029
	Contact Switching Load (Min)	.1mA @ .0001V
	Contact Limiting Breaking Current (A)	2
	Coil Power Rating Class	50 – 300mW
	Coil Type	Monostable
	Voltage Standing Wave Ration (HF Parameter)	1.06 @ 100MHz, 1.49 @ 900Mhz
Signal Characteristics	Isolation (HF Parameter)	-37dB @ 100MHz, -18.8dB @ 900MHz
	Insertion Loss (HF Parameter)	-.33dB @ 900MHz, -.03dB @ 100MHz
Body Features	Insulation Special Features	2500V Initial Surge Withstand Voltage between Contacts & Coil
Contact Features	Terminal Type	PCB-SMT
	Contact Current Rating (A)	2
	Contact Arrangement	2 Form C (CO)
	Contact Material	PdRu
	Contact Number of Poles	2
	Contact Special Features	Bifurcated/Twin Contacts
	Contact Current Class	0 – 2 A

	Contact Plating Material	Gold
Mechanical Attachment	Mounting Type	Printed Circuit Board
Dimensions	Length Class (Mechanical)	0 – 10 mm
	Width Class (Mechanical)	0 – 6 mm
	Length (in)	10
	Width	6 mm [.236 in]
	Height Class (Mechanical)	0 – 6 mm
	Dimensions (L x W x H) (Approximate)	10 x 6 x 5.65 mm [.393 x .236 x .222 in]
	Height	5.6 mm [.221 in]
Usage Conditions	Environmental Category of Protection	RTV
	Environmental Ambient Temperature (Max)	85 °C [85 °F]
	Environmental Ambient Temperature Class	70 – 85°C
Operation/Application	Performance Type	High Dielectric
Packaging Features	Packaging Method	Reel
Other	Additional Features	Gull Wing
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

SURFACE MOUNT RESISTORS




SMF3 27K 5%
SMF327KJT

Save to List

Find Similar Products


CHASSIS PANEL MOUNT RESISTORS



THS15 150R 5%
THS15150RJ

Save to List

Find Similar Products




RP 1J 0.166W 90K9 0.1%
25PPM 1K RL
8-2176089-6

Save to List

Find Similar Products

TACTILE SWITCHES



FSM2JSMLS=6MM TACT
SWITCH, SMT 100gf
1977223-1

Save to List

Find Similar Products

