

• Products

- O <u>By Type</u>
 - Connectors
 - Electromechanical Components
 - Electronic Modules
 - Fiber Optics
 - Filters
 - Identification & Labeling •
 - Passive Components
 - Power Sources
 - RF & Microwave Products
 - Tooling Products
 - Touch Screen Displays
 - Tubing, Molded and Harnessing Products Wire, Cable and Cable Assemblies
 - List all product types...
- O By Industry
 - Aerospace & Defense Products
 - Appliance
 - Automotive
 - Communications
 - Computer & Consumer Electronics
 - Industrial & Commercial Instrumentation & Medical
- O By Brand 0 A to Z
- O <u>Product News</u>

Documentation

- O Find Documents & Drawings
- Find CAD Models 0
- 0 SPICE/Electrical Models
- 0 NAFTA Certificate of Origin
- O White Papers

Resources

- O RoHS Compliance & Alternates
- O <u>Cross Reference Products</u>
- O <u>Compare Multiple Products</u>
- O Check Distributor Inventory
- O Find Authorized Distributors

• My Account

- O Sign In
- O Register

<u>Customer Support</u>

- O Support
- O <u>RoHS Support Center</u>
- O Glossary of Terms
- O <u>eBulletin Newsletter</u>

T90N1D12-12 Product Details



Active

Power PC Board Relays

Converted to EU RoHS but not ELV Compliant (Statement of Compliance)



T90 Series

- Contact Arrangement = 1 Form A, SPST-NO, 1 N/O
- Contact Current Rating = 30 Amps.
- Monostable Coil Magnetic System •
- Without Coil Suppression Diode

View all Features | Find Similar Products

Documentation & Additional Information



None Available

Catalog Pages/Data Sheets:

• T90 30 Amp Printed Circuit Board Relay (PDF, English)

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

Product Line Information

Quick Links

•

.

• •

Previous 1 ... 6 7 8 [9] 10 ... 20 Next

Check Pricing & Availability

Contact Us About This Product

Search for Tooling

Compare Products

Product Feature Selector

Additional Product Images:

- Schematic
- PCB Layout ٠
- Wiring Diagram ٠

Related Products:

• <u>Tooling</u>

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

• <u>Termination Type</u> = Through Hole

Electrical Characteristics:

- <u>Contact Current Rating (Amps.)</u> = 30
- . Coil Resistance (?) = 155
- ٠ Coil Power, Nominal (mW) = 930
- Actuating System=DC
- Input Voltage (VDC) = 12 ٠

Body Related Features:

- <u>Series</u> = T90
- Polarized = No •

Contact Related Features:

- <u>Mounting Options</u> = PC Board
- Enclosure = Open
- ٠ FCC Part 68 Isolation = No
- Relay Type = PCB
- Contact Material = Silver Cadmium Oxide
- Approx. Dimensions (L x W x H) (mm[in]) = 30.50 x 24.10 x 16.90 [1.201
- x .949 x .665] Wiring Diagram=1 FormC
- Approved Standards = UL Recognized, CSA Component Acceptance, CSA Certified

Configuration Related Features:

- Contact Arrangement = 1 Form A, SPST-NO, 1 N/O
- Coil Magnetic System = Monostable
- Coil Suppression Diode = Without
- Coil Selection Criteria = Nominal Voltage
- Coil Latching = Without
- LED Indicator = Without ٠

Industry Standards:

- <u>RoHS/ELV Compliance</u> = RoHS/Not ELV Compliant
- Lead Free Solder Processes = Wave solder capable to 240C, Wave solder capable to 260C
- RoHS/ELV Compliance History = Converted to comply with RoHS not ELV directives
- Coil Insulation Classification = UL Class F .

Other:

٠ Brand = Potter & Brumfield 2008 Tyco Electronics Corporation All Rights Reserved