



KEMET Part Number: ESY477M010AG3AA
(ESY477M010AG3AAPLP)



Aluminum Electrolytic, 105C LowZ, KEMET, ESY, 470 uF, 20%, 10 V, -40/+105C, 11mm, Lead Spacing = 3.5mm



Note: '()' correspond to the letters used in the product bulletin

Dimensions

D	8mm +/-0.5mm
L	11mm +1.5mm
S	3.5mm +/-0.5mm
LL Negative	15mm MIN
LL Positive	20mm MIN
F	0.6mm NOM

Packaging Specifications

Packaging:	Bulk, Bag
Packaging Quantity:	6000

General Information

Dielectric:	Aluminum Electrolytic
Supplier:	KEMET
Series:	ESY
Description:	LowZ Single Ended Aluminum Electrolytic
Features:	Low Z
RoHS:	Yes
Lead:	Wire Leads

Specifications

Capacitance:	470 uF
Capacitance Tolerance:	20%
Voltage DC:	10 VDC, 13 VDC (Surge)
Temperature Range:	-40/+105C
Rated Temperature:	105C
Life:	3000 Hrs
Dissipation Factor:	19%
Resistance:	0.072 Ohms (100kHz)
Current:	760 mAmps (100kHz 105C)
Leakage:	47 uAmps (2min 20C)
Impedance Ratio at -25C:	3
Impedance Ratio at -40C:	2

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006 - 2016 IntelliData.net