

**KEMET Part Number: PEH534YDG3470M2**  
(A561EH471M450A)

Aluminum Electrolytic, 105C, KEMET, PEH534, 470 uF, 20%, 450 V, -40/+105C



**Dimensions**

<b>D</b>	35mm +1mm
<b>L</b>	50mm +/-2mm
<b>S</b>	10mm +/-0.1mm
<b>LL</b>	6.3mm +/-1mm
<b>F</b>	2mm +/-0.1mm

**Packaging Specifications**

<b>Weight:</b>	72 g
<b>Packaging:</b>	Bulk
<b>Packaging Quantity:</b>	100

**General Information**

<b>Dielectric:</b>	Aluminum Electrolytic
<b>Supplier:</b>	KEMET
<b>Series:</b>	PEH534
<b>Description:</b>	Snap-In, Aluminum Electrolytic
<b>RoHS:</b>	Yes
<b>Lead:</b>	2 Pin
<b>Notes:</b>	Add 0.5mm To D And 1mm To L For Sleeving

**Specifications**

<b>Capacitance:</b>	470 uF
<b>Capacitance Tolerance:</b>	20%
<b>Voltage DC:</b>	450 VDC
<b>Temperature Range:</b>	-40/+105C
<b>Rated Temperature:</b>	105C
<b>Life:</b>	3000 Hrs (Rated Voltage And Ripple Current At 105C), 4000 Hrs (Rated Voltage At 105C)
<b>Resistance:</b>	180 mOhms (100Hz 20C), 110 mOhms (100kHz 20C)
<b>Current:</b>	1.9 Amps (100Hz 105C), 12.4 Amps (20kHz 40C)
<b>Leakage:</b>	635 uAmps (5min 20C)