Molex.com

English 日本部 行 简体中文 Search site:Search: Enter Part No. or k

Cross-Ref Catalog Literature

Product Name

Industries Standards

Contact Us About Us

Investors Careers

Connectors

Sockets

I/O Connectors

Cable

Fiber Optics

Printed Circ

Industrial

Lighting Products

Register | Login

My Parts (0 items)

Switch Language

English

Need Assistance?

Contact Us
Find a Distributor
Order Samples
Tech Library
Ecocare
Electrical Models

Printer-friendly page

Email this page

Home

<u>Crimp Housings</u> Datasheet

Part Number:

0003091049

Status:

Active


Overview:

Standard .093"

Description:

2.36mm (.093") Diameter Standard .093 Pin and Socket Receptacle Housing, 4 Circuits, Dual Row

Documents: Note - Please disable browser pop-up blockers for documents on www.molex.com
Drawing (PDF)
Product Specification PS-02-09 (PDF)



EU RoHS

ELV and RoHS Compliant

REACH SVHC

Contains SVHC: No

Halogen-Free Status

Halogen-Free



Molex Connector Part Number - 0003091049	
_	

Need more information on product
environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

2163Series

Mates With

2163p

Use With

1189 Crimp Terminals, 1190 Crimp Terminals, 1376 Male PC Tail Terminals, 1380 Male Crimp Terminals, 1380 Male Crimp Terminals, 1381 Female Crimp Terminals, 1433 Crimp Terminals, 1434 Male Crimp Terminals, 1973, 2151, 2273, 2870, 2871, 4272, 4550, 6271, 6310, 42477, 42478

Product Specification PS-43660-9999 (PDF)

3E

Order Products:

Part Detail: (show all)

GeneralPhysicalElectricalAgency CertificationMaterial InfoReference - Drawing Numbers

Ge	n	ρ	ra

Product Family Series	Crimp Housings 2163
Comments	14.0A max. can be achieved when housing is used with 42477 or 42478 terminals
Overview	Standard .093"
Product Name	Standard .093"

Physical

Circuits (maximum)	4
Circuits Detail	(2 x 2)
Color - Resin	Natural
Flammability	94V-2
Gender	Dual
Glow-Wire Compliant	No
Material - Resin	Nylon
Number of Rows	2
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface (in)	0.198 In
Pitch - Mating Interface (mm)	5.03 mm
Stackable	No
Temperature Range - Operating	-40°C to +105°C

Electrical(Please review the Product Specification for specific details.)

Current - Maximum per Contact 11A

Agency Certification

CSA	LR19980
UL	E29179

Material Info

Old Part Number	2163-R1
-----------------	---------

Reference - Drawing Numbers

Product Specification	PS-02-09, PS-43660-9999
Sales Drawing	SD-2163-*

Feedback Privacy Legal Site Map

Help

