Molex.com

English 당초평 Register | Login で 管体中文 My Parts (0 items) Search site:Search: Enter Part No. or K Go

Product Name

Cross-Ref

Catalog

Literature Industries

Standards

Contact Us

About Us

Investors

Careers

Switch Language

English

Need Assistance?

Contact Us Find a Distributor **Order Samples Tech Library** Ecocare **Electrical Models**

Printer-friendly page

Email this page

Home

Crimp Housings

Datasheet

Part Number:

0039014053

Status:

Active

Overview:

Mini-Fit Jr.™

Description:

4.20mm (.165") Pitch Mini-Fit Jr.™ Plug Housing, Single Row, with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 5 Circuits


Documents: Note - Please disable browser pop-up blockers for documents on www.molex.com Product Specification PS-5556-001 (PDF) Drawing (PDF)

3D

EU RoHS ELV and RoHS Model Compliant

> **REACH SVHC** Not Reviewed

Halogen-Free Status Halogen-Free







Molex Connector Part Numbe	r - 0039014053	Page
		Need more information on product environmental compliance?
		Email productcompliance@molex.com
		For a multiple part number RoHS Certificate of Compliance, click here
		Please visit the <u>Contact Us</u> section for any non-product compliance questions.
		1
		Search Parts in this Series <u>5559</u> Series
		Mates With 39-01-4051 Crimp Housing
		Use With 5558 Mini-Fit Jr.™ Male Crimp Terminals 44478 Mini-Fit HCS™ Male Crimp Terminals 30490 Mini-Fit® Male Grounding Crimp Terminals
	Order Products:	
	Part Detail: (show all)	
	GeneralPhysicalElectricalAgency CertificationMaterial InfoReference - Drawing Numbers	

Page 2 of 4

_	_		_	
(9	e	n	e	ra

Product Family Series	Crimp Housings 5559
Comments	Current = 13A max. per circuit when header is mated to a receptacle loaded with <u>45750</u> series terminals crimped to 16 AWG wire. See Molex product specification PS-45750-001 for additional current de-rating information.
Overview	<u>Mini-Fit Jr.™</u>
Product Name	Mini-Fit Jr.™

Physical

Breakaway	No
Circuits (maximum)	5
Color - Resin	Natural
Flammability	94V-0
Gender	Male
Glow-Wire Compliant	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Resin	Nylon
Number of Rows	1
Packaging Type	Bag
Panel Mount	Yes
Pitch - Mating Interface (in)	0.165 ln
Pitch - Mating Interface (mm)	4.20 mm
Pitch - Term. Interface (in)	0.165 ln
Pitch - Term. Interface (mm)	4.20 mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40°C to +105°C

Electrical(Please review the Product Specification for specific details.)

Current - Maximum per Contact	13A	
-------------------------------	-----	--

Agency Certification

CSA	LR19980
TUV	R72081037
UL	E29179

Material Info

Old Part Number	5559-05P2-210	

Reference - Drawing Numbers

Product Specification PS-5556-001
Sales Drawing SD-5559-NLP*

Feedback Privacy Legal Site Map Help

