

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [19429-0016](#)  
**Status:** **Active**  
**Overview:** MX150L™ Industrial Sealed Connector System  
**Description:** MX150L™ 16 Circuit Panel Mount Plug for 14-22 AWG Wire, Rear Mount Flange Assembly, without Gasket

**Documents:**

[3D Model](#) [RoHS Certificate of Compliance \(PDF\)](#)  
[Drawing \(PDF\)](#) [Product Literature \(PDF\)](#)  
[Product Specification PS-19417-001 \(PDF\)](#)

**General**

|                             |   |
|-----------------------------|---|
| Product Family              | Crimp Housings  |
| Series                      | <a href="#">19429</a>   |
| Application                 | Power, Wire-to-Wire   |
| Comments                    | For Inside Panel Mount Application. IP67 rated; conforms to UL 1977. NOT suitable for automotive applications with requirements such as USCAR-2, USCAR-25, GMW3191, AK Testing, J2030, Volvo Technology Requirements, and Toyota Connector Spec (TCS) |
| Overview                    | <a href="#">MX150L™ Industrial Sealed Connector System</a>  |
| Product Literature Order No | 987650-2181   |
| Product Name                | MX150L™   |
| UPC                         | 822348543496  |

**Physical**

|                               |                 |
|-------------------------------|-----------------|
| Circuits (maximum)            | 16              |
| Gender                        | Plug            |
| Glow-Wire Compliant           | No              |
| Lock to Mating Part           | Yes             |
| Net Weight                    | 24.763/g        |
| Number of Rows                | 2               |
| Packaging Type                | Bag             |
| Panel Mount                   | Yes             |
| Pitch - Mating Interface      | 5.84mm          |
| Polarized to Mating Part      | Yes             |
| Stackable                     | No              |
| Temperature Range - Operating | -40°C to +125°C |

**Electrical**

|                               |     |
|-------------------------------|-----|
| Current - Maximum per Contact | 18A |
|-------------------------------|-----|

**Material Info**

**Reference - Drawing Numbers**

|                       |              |
|-----------------------|--------------|
| Product Specification | PS-19417-001 |
| Sales Drawing         | SD-19429-008 |



|  |                       |
|--|-----------------------|
| <b>EU RoHS</b><br>ELV and RoHS<br>Compliant<br>REACH SVHC<br>Contains SVHC: No<br>Low-Halogen Status<br>Not Reviewed | <b>China RoHS</b><br> |
|--|-----------------------|

**Need more information on product environmental compliance?**  
 Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 For a multiple part number RoHS Certificate of Compliance, [click here](#)  
 Please visit the [Contact Us](#) section for any non-product compliance questions.

|   |
|---|
| <b>Search Parts in this Series</b><br><a href="#">19429Series</a> |
| <b>Mates With</b><br><a href="#">19418 Receptacle Assemblies</a>  |
| <b>Use With</b><br><a href="#">19417 Male Crimp Terminals</a>     |