

[Molex.com](#)

English  
日本語  
한국어  
简体中文

[Register | Login](#)  
[My Parts \( 0 items \)](#)

Search site:Search:  [Go](#)

- Product Name
- Cross-Ref
- Catalog
- Literature
- Industries
- Standards
- Contact Us
- About Us
- Investors
- Careers

- Connectors
- Sockets
- I/O Connectors
- Cable Assemblies
- Fiber Optics
- Printed Circuit Products
- Industrial Products
- Lighting Products

**Switch Language**

English

- [Home](#)
- [Quick Disconnects](#)
- [Datasheet](#)

**Need Assistance?**

- Contact Us
- Find a Distributor
- Order Samples
- Tech Library
- Ecocare
- Electrical Models

[Printer-friendly page](#)

[Email this page](#)

**Part Number:**

**0197054103**

**Status:**

**Active**


**Description:**

PCB Tab Quick Disconnect, Male, for Wire, Metal Strip, Tab 4.75mm (.187") x 0.81mm (.032")

**Documents:** [Note - Please disable browser pop-up blockers for documents on www.molex.com](#)

[Drawing \(PDF\)](#)

[Product Specification PS-19708-001 \(PDF\)](#)



Series image - Reference only

**EU RoHS**  
ELV and RoHS  
Compliant

**REACH SVHC**  
Contains SVHC: No

**Halogen-Free**  
Status  
Not Reviewed

**China RoHS**



**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**

19705Series

[Datasheet \(PDF\)](#)

[RoHS](#)

**Order Products:**

**Part Detail: ([show all](#))**

[General](#)[Physical](#)[Electrical](#)[Agency Certification](#)[Material Info](#)[Reference - Drawing Numbers](#)

**General**

Product Family	Quick Disconnects
Series	<u>19705</u>
Comments	Tab Support
Product Name	PCB Tab
Type	Quick Disconnect

**Physical**

Barrel Type	Closed
Gender	Male
Glow-Wire Compliant	No
Insulation	None
Lock to Mating Part	None
Material - Metal	Brass
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Orientation	PCB Straight Tab
Packaging Type	Reel
Plating min: Mating ( $\mu$ in)	150
Plating min: Mating ( $\mu$ m)	3.81
Plating min: Termination ( $\mu$ in)	150
Plating min: Termination ( $\mu$ m)	3.81
Polarized to Mating Part	No
Tab Thickness	0.81mm (.032")
Tab Width	4.75mm (.187")
Wire Insulation Diameter	N/A
Wire Size AWG	N/A

**Electrical**(Please review the Product Specification for specific details.)

Voltage - Maximum	N/A
-------------------	-----

**Agency Certification**

UL	E79133
----	--------

**Material Info****Reference - Drawing Numbers**

Product Specification	PS-19708-001
Sales Drawing	SD-19705-400

