Molex.com

Register | Login My Parts (0 items)

Product Name Cross-Ref Catalog Literature

Search site:Search: Enter Part No. or K Go

Industries

Standards **Contact Us About Us**

Investors

Careers

Switch Language

English

Need Assistance?

Contact Us Find a Distributor **Order Samples Tech Library** Ecocare **Electrical Models**

Printer-friendly page

Email this page

Home

English 당초병

ごって 简体中文

PCB Receptacles

Datasheet

Part Number:

0714393864

Status:


Active

Description:

1.00mm (.039") Pitch Mezzanine IEEE 1386 Receptacle, Surface Mount, Dual Row, Vertical Stacking, Embossed Tape on Reel, 0.76µm (30µ") Gold (Au), 64 Circuits Pick and Place Cap

Documents: Note - Please disable browser pop-up blockers for documents on www.molex.com

Drawing (PDF) Product Specification PS-71436-9999 (PDF)



China RoHS

<u>3D</u> Model

EU RoHS

ELV and RoHS Compliant

REACH SVHC

Contains SVHC: No

Halogen-Free Status

Halogen-Free

Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

71439Series

Mates With

714361 for Stack Height 14.00mm (.551"), 714362 for Stack Height 15.00mm (.591")

Order Products:

Part Detail: (show all)

GeneralPhysicalElectricalAgency CertificationSolder Process DataMaterial InfoReference - Drawing Numbers

General

Product Family	PCB Receptacles
Series	<u>71439</u>
Application	Board-to-Board
Comments	Plugs
Product Name	Mezzanine

		CI	2
	nv		
-	,		

Filysical	
Circuits (Loaded)	64
Color - Resin	Natural
Flammability	94V-0
Glow-Wire Compliant	No
Lock to Mating Part	Yes
Mated Height (in)	0.551 ln, 0.591 ln
Mated Height (mm)	14.00 mm, 15.00 mm
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Number of Rows	2
Orientation	Vertical
PCB Locator	Yes
PCB Retention	None
Packaging Type	Embossed Tape on Reel
Pitch - Mating Interface (in)	0.039 In
Pitch - Mating Interface (mm)	1.00 mm
Plating min: Mating (µin)	30.4
Plating min: Mating (µm)	0.76
Plating min: Termination (µin)	76.4
Plating min: Termination (µm)	1.91
Polarized to PCB	No
Robotic Placement	Pick and Place Cap
Surface Mount Compatible (SMC)	N/A
Temperature Range - Operating	-55°C to +85°C
Termination Interface: Style	Surface Mount

Electrical(Please review the Product Specification for specific details.)

Current - Maximum per Contact	1A
Voltage - Maximum	100V

Agency Certification

CSA	LR19980
UL	E29179

Solder Process Data

Lead-free Process Capability	Reflow Capable (SMT only)
Process Temperature max. C	260

Material Info

Reference - Drawing Numbers

Product Specification PS-71436-9999
Sales Drawing SDA-71439-3***

Feedback Privacy Legal Site Map Help

