

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: **0760351103**

Status: **Active**

Overview:

Description: 1.85mm by 3.70mm (.073" by .146") Pitch, GbX I-Trac™ Vertical Header Module, Unguided, Open Ends, 15 Rows, 10 Columns, 300 Circuits, Mating Pin Length 4.70mm (.185")

Documents:

[3D Model](#)

[Packaging Specification \(PDF\)](#)

[Drawing \(PDF\)](#)

[Product Specification PS-75710-999 \(PDF\)](#)


[RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family	Backplane Connectors
Series	76035
Application	Backplane
Application	Midplane
Application	Orthogonal
Application Tooling Documents	Tooling Manual
Component Type	PCB Header
More Detailed Tech Information	I-Trac@molex.com
Overview	GbX I-Trac™; Backplane Connector System
Product Name	GbX I-Trac™
Style	N/A

Physical

Circuits (Loaded)	300
Circuits (maximum)	300
Color - Resin	Black
Durability (mating cycles max)	200
First Mate / Last Break	No
Flammability	94V-0
Guide to Mating Part	No
Keying to Mating Part	None
Material - Metal	High Performance Alloy (HPA)
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Number of Columns	10
Number of Pairs	8
Number of Pairs	Open Pin Field
Number of Rows	15
Orientation	Vertical
PC Tail Length (in)	0.083 In
PC Tail Length (mm)	2.10 mm
PCB Locator	No
PCB Retention	None
PCB Thickness Recommended (in)	0.063 In
PCB Thickness Recommended (mm)	1.60 mm
Packaging Type	Tray
Pitch - Mating Interface (in)	0.073 In
Pitch - Mating Interface (in)	0.146 In
Pitch - Mating Interface (mm)	1.85 mm
Pitch - Mating Interface (mm)	3.70 mm
Pitch - Term. Interface (in)	0.039 In
Pitch - Term. Interface (in)	0.106 In



Series image - Reference only

EU RoHS

ELV and RoHS Compliant

REACH SVHC

Contains SVHC: No

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

76035 Series

Mates With

76040 GbX I-Trac™ Right Angle Receptacle Module

Use With

78237 GbX I-Trac™ Vertical Power Receptacle. 75234 Backplane Free Standing Guide Pin

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
Press-In Tool, GbX I-Trac™ Vertical Header 15 Row, 10 Column	0622018621
Backplane Insertion Tool, GbX I-Trac™	0621005110

Pitch - Term. Interface (mm)	1.00 mm
Pitch - Term. Interface (mm)	2.70 mm
Plating min: Mating (µin)	30.4
Plating min: Mating (µm)	0.76
Plating min: Termination (µin)	30.4
Plating min: Termination (µm)	0.76
Polarized to PCB	No
Stackable	Yes
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	-55°C to +80°C
Termination Interface: Style	Through Hole - Compliant Pin

Signal Contact Insertion

Electrical

Current - Maximum	1A
Data Rate	12.0 Gbps
Real Signals (per 25mm)	202
Shield Type	N/A
Shielded	No
UL	E29179
Voltage - Maximum	120V AC (RMS)/DC

Material Info**Reference - Drawing Numbers**

Product Specification	PS-75710-999
Sales Drawing	SD-76035-001

This document was generated on 12/01/2009

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION