

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0763525001](#)

Status: **Active**

Overview:

Description: Small Form-factor Pluggable Plus (SFP+) Stacked 2-by-8 Multi-Port Connector with 4 Lightpipe Ports, EMI Metal Gasket, 320 Circuits, Tin (Sn) Tails

Documents:

[Packaging Specification \(PDF\)](#)

[Drawing \(PDF\)](#)

[3D Model](#)

[Application Specification \(PDF\)](#)

[Product Specification PS-75310-001 \(PDF\)](#)


[RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family	I/O Connectors
Series	76352
Application	Module-to-Board
Component Type	Receptacle
Overview	SFP+; Stacked Multi-Port Connectors
Product Name	SFP Plus
Type	N/A

Physical

Boot Color	N/A
Circuits (Loaded)	320
Circuits (maximum)	320
Circuits Detail	320
Color - Resin	Black
Color - Resin	Clear (Blue Tint)
Durability (mating cycles max)	100
Flammability	94V-0
Gender	Female
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Metal	Brass
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Material - Resin	Polycarbonate
Number of Rows	2
Orientation	Right Angle
PC Tail Length (in)	0.081 In
PC Tail Length (mm)	2.07 mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness Recommended (in)	0.062 In
PCB Thickness Recommended (mm)	1.57 mm
Packaging Type	Tray
Panel Mount	No
Pitch - Mating Interface (in)	0.031 In
Pitch - Mating Interface (mm)	0.80 mm
Pitch - Term. Interface (in)	0.031 In
Pitch - Term. Interface (mm)	0.80 mm
Plating min: Mating (µin)	30.4
Plating min: Mating (µm)	0.76
Plating min: Termination (µin)	30.4
Plating min: Termination (µm)	0.76
Polarized to Mating Part	Yes



Series image - Reference only

EU RoHS

ELV and RoHS Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[76352 Series](#)

Use With

[0759510999 SFP Dust Plug,](#)

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
Insertion Tool for 2-by-8 Small Form-Factor Pluggable (SFP+)	0622029810
Removal Tool for 2-by-8 Small Form-Factor Pluggable (SFP+)	0622029820

Polarized to PCB	Yes
Ports	16
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-40°C to +85°C
Termination Interface: Style	Through Hole - Compliant Pin
Waterproof / Dustproof	No

Electrical

CSA	LR19980
Current - Maximum	0.5A
Grounding to Panel	None
Shield Type	EMI Gasket
Shielded	Yes
Voltage - Maximum	120V AC (RMS)/DC

Material Info**Reference - Drawing Numbers**

Product Specification	PS-75310-001
Sales Drawing	SD-76352-001

This document was generated on 11/19/2009

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION