



- NOTES:
1. MATERIAL: SEE TABLE
 2. FINISHES: SEE TABLE
 3. PRODUCT SPECIFICATION: NOT REQUIRED
 4. PACKAGING: NOT REQUIRED
 5. MATES WITH: NONE
 6. "XX" REFERS TO THE QUANTITY OF CIRCUIT POSITIONS.

NUMBER OF CIRCUITS "XX"	DIM "A"	DIM "B"	STANDARD MATERIAL NO.	-50 OPTION MATERIAL NO.
02	18.5 (.73)	8.26 (.325)	387006302	387007502
03	26.9 (1.06)	16.51 (.650)	387006303	387007503
04	35.1 (1.38)	24.77 (.975)	387006304	387007504
05	43.2 (1.70)	33.02 (1.300)	387006305	387007505
06	51.2 (2.03)	41.28 (1.625)	387006306	387007506
07	59.7 (2.35)	49.53 (1.950)	387006307	387007507
08	68.1 (2.68)	57.79 (2.275)	387006308	387007508
09	76.2 (3.00)	66.04 (2.600)	387006309	387007509
10	84.6 (3.33)	74.30 (2.925)	387006310	387007510
11	92.7 (3.65)	82.55 (3.250)	387006311	387007511
12	101.0 (3.98)	90.81 (3.575)	387006312	387007512
13	109.2 (4.30)	99.06 (3.900)	387006313	387007513
14	117.5 (4.63)	107.32 (4.225)	387006314	387007514
15	125.7 (4.95)	115.57 (4.550)	387006315	387007515
16	134.0 (5.28)	123.83 (4.875)	387006316	387007516
17	142.2 (5.60)	132.80 (5.200)	387006317	387007517
18	150.5 (5.93)	140.34 (5.525)	387006318	387007518
19	158.8 (6.25)	148.59 (5.850)	387006319	387007519
20	167.0 (6.58)	156.85 (6.175)	387006320	387007520
21	175.3 (6.90)	165.10 (6.500)	387006321	387007521
22	183.5 (7.23)	173.36 (6.825)	387006322	387007522
23	191.8 (7.55)	181.61 (7.150)	387006323	387007523
24	200.0 (7.88)	189.87 (7.475)	387006324	387007524
25	208.3 (8.20)	198.12 (7.800)	387006325	387007525
26	216.5 (8.53)	206.38 (8.125)	387006326	387007526
27	224.8 (8.85)	214.63 (8.450)	387006327	387007527
28	233.0 (9.18)	222.89 (8.775)	387006328	387007528
29	241.3 (9.50)	231.14 (9.100)	387006329	387007529
30	249.6 (9.83)	239.40 (9.425)	387006330	387007530

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
4	"XX"	SCREW, #6-32, PAN HD, PH-SL, W/SB WASHER	STEEL	ZN, CLEAR CHROMATE
3	"XX"	SCREW, #6-32, PAN HD, PH-SL	STEEL	ZN, CLEAR CHROMATE
2	"XX"	TERMINAL	BRASS	TIN
1	1	BARRIER	THERMOPLASTIC	BLACK

EC NO. 3712
 DRWN: CY 05-28-04
 CH'K:
 APPR:
 REV B

QUALITY SYMBOLS:
 MAJOR =
 CRITICAL =
 SPC =

GENERAL TOLERANCES: (UNLESS SPECIFIED)

	mm	INCH
4 PLACES		±.0015
3 PLACES	±.038	±.005
2 PLACES	±.13	±.01
1 PLACE	±.3	

ANGULAR: ±2°

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

SCALE: 2:1

DESIGN UNITS:
 mm INCH

THIRD ANGLE PROJECTION

DRAWN BY & DATE:
 R. KEMP 07-16-03

CHECKED BY & DATE:
 R. STONE 07-16-03

APPROVED BY & DATE:
 P. WALTZ 07-17-03

CAD FILENAME: 705XX-C

PROJECT NO. -

DIMENSIONS:
 mm INCH mm ONLY

REVISIONS:
 SHT REV
 REVISE ON CAD ONLY

TITLE:
 SR BTS ASSY, PC, NO MTG.

MOLEX INCORPORATED

MATERIAL NO. SEE CHART
 DRAWING NO. SD-38700-001
 SHEET NO. 1 OF 1
 SIZE B