



Specifications

| Items | Specifications | | |
|----------------------------|---|---|---------------|
| Size code | B2 | D2E | D3L |
| Category temperature range | -55 to +105 °C | | |
| Rated voltage range | 2.5 to 10 V.DC | | |
| Rated capacitance range | 47 to 100 μF | 68 to 470 μF | 150 to 680 μF |
| Capacitance tolerance | ±20 % (120 Hz/+20 °C) | | |
| Leakage current | Please see the attached characteristics list | | |
| Dissipation factor(tan δ) | Please see the attached characteristics list | | |
| Surge voltage | Rated voltage x1.15 | | |
| Endurance | 105 °C, 2,000 h, (B2 size : 1,000 h)rated voltage applied | | |
| | ΔC/C | Within±20 % of the initial value | |
| | DF | ≤1.5 times of the initial limit | |
| | LC | Within the initial limit | |
| Damp heat (Steady State) | 85 °C, 85 to 90 %RH, 500 h, rated voltage applied | | |
| | ΔC/C | Within +50 %, -20 % of the initial value(2R5TAE470M(F), 2R5TAE330M(F, I), 2R5TAE220M(F, 9)) | |
| | DF | ≤ 1.5 times of the initial limit | |
| | LC | Within the initial limit | |

Marking and dimensions

D2E, D3L Size

R. Capacitance

Polarity marking (+)

Lot. No.

R. Voltage code

B2 Size

R. Capacitance code

Polarity marking (+)

Lot. No.

R. Voltage code

(unit : mm)

| Size code | L ±0.3 ※1 | W ±0.2 | H ±0.2 ※2 | S ±0.2 | W1 ±0.1 |
|-----------|-----------|--------|-----------|--------|---------|
| B2 | 3.5 | 2.8 | 1.9 | 0.8 | 2.2 |
| D2E | 7.3 | 4.3 | 1.8 | 1.3 | 2.4 |
| D3L | 7.3 | 4.3 | 2.8 | 1.3 | 2.4 |

※1 ±0.2: B2 ※2 ±0.1: B2, D2E

| R. Voltage (V.DC) | 2.5 | 4.0 | 6.3 | 10.0 |
|-------------------|-----|-----|-----|------|
| Code | e | g | j | A |

B2 size

| R. Cap. (μF) | 47 | 68 | 100 |
|--------------|----|----|-----|
| Code | S7 | W7 | A8 |

Characteristics list

| Series | Rated voltage (V.DC) | Rated temp. (°C) | Category voltage (V.DC) | Category temp. (°C) | Rated capacitance (μF) | Case size (mm) | | | Size code | Specifications | | | | Standard | |
|--------|----------------------|------------------|-------------------------|---------------------|------------------------|----------------|--------------|------|-----------|--|------------------|----------|------------|-------------|--------------------------|
| | | | | | | L | W | H | | Maximum allowable ripple current (mA rms) 100 kHz ※1 | ESR ※2 (mΩ max.) | tan δ ※3 | LC ※4 (μA) | Part number | Min. Packaging Qty (pcs) |
| TA | 2.5 | 105 | 2.5 | 105 | 220 | 7.3 | 4.3 | 1.8 | D2E | 3900 | 9 | 0.10 | 110.0 | 2R5TAE220M9 | 3000 |
| | | | | | | | | | | 3100 | 15 | 0.10 | 55.0 | 2R5TAE220MF | 3000 |
| | | | | | | | | | | 2400 | 25 | 0.10 | 55.0 | 2R5TAE220M | 3000 |
| | | 3100 | 15 | 0.10 | 82.5 | 2R5TAE330MF | 3000 | | | | | | | | |
| | | 2800 | 18 | 0.10 | 82.5 | 2R5TAE330MI | 3000 | | | | | | | | |
| | | 2400 | 25 | 0.10 | 82.5 | 2R5TAE330M | 3000 | | | | | | | | |
| | | D2E | 3100 | 15 | 0.10 | 117.5 | 2R5TAE470MF | 3000 | | | | | | | |
| | | | 2400 | 25 | 0.10 | 117.5 | 2R5TAE470M | 3000 | | | | | | | |
| | | | 3100 | 15 | 0.10 | 170.0 | 2R5TAE680MFL | 2500 | | | | | | | |
| | | | 2400 | 25 | 0.10 | 170.0 | 2R5TAE680ML | 2500 | | | | | | | |
| | | | 1100 | 70 | 0.08 | 40.0 | 4TAB100M | 2000 | | | | | | | |
| | | | 2800 | 18 | 0.10 | 88.0 | 4TAE220MI | 3000 | | | | | | | |
| | 4 | 105 | 4.0 | 105 | 220 | 7.3 | 4.3 | 1.8 | D2E | 2400 | 25 | 0.10 | 88.0 | 4TAE220M | 3000 |
| | | | | | | | | | | 2800 | 18 | 0.10 | 188.0 | 4TAE470MIL | 2500 |
| | | | | | | | | | | 2400 | 25 | 0.10 | 188.0 | 4TAE470ML | 2500 |
| | | D3L | 2400 | 25 | 0.10 | 188.0 | 4TAE470ML | 2500 | | | | | | | |
| | | | 1100 | 70 | 0.08 | 29.6 | 6TAB47M | 2000 | | | | | | | |
| | | | 2800 | 18 | 0.10 | 138.6 | 6TAE220MI | 3000 | | | | | | | |
| | 6.3 | 105 | 6.3 | 105 | 47 | 3.5 | 2.8 | 1.9 | B2 | 1100 | 70 | 0.08 | 42.8 | 6TAB68M | 2000 |
| | | | | | | | | | | 2400 | 25 | 0.10 | 94.5 | 6TAE150M | 3000 |
| | | | | | | | | | | 2800 | 18 | 0.10 | 138.6 | 6TAE220MI | 3000 |
| | | D2E | 2400 | 25 | 0.10 | 138.6 | 6TAE220M | 3000 | | | | | | | |
| | | | 2400 | 25 | 0.10 | 207.9 | 6TAE330ML | 2500 | | | | | | | |
| | | | 1100 | 70 | 0.08 | 47.0 | 10TAB47M | 2000 | | | | | | | |
| 10 | 105 | 10.0 | 105 | 47 | 3.5 | 2.8 | 1.9 | B2 | 2400 | 25 | 0.10 | 68.0 | 10TAE68M | 3000 | |
| | | | | | | | | | 2400 | 25 | 0.10 | 150.0 | 10TAE150ML | 2500 | |
| | | | | | | | | | 2400 | 25 | 0.10 | 220.0 | 10TAE220ML | 2500 | |
| | D2E | 2400 | 25 | 0.10 | 68.0 | 10TAE68M | 3000 | | | | | | | | |
| | | 2400 | 25 | 0.10 | 150.0 | 10TAE150ML | 2500 | | | | | | | | |
| | | 2400 | 25 | 0.10 | 220.0 | 10TAE220ML | 2500 | | | | | | | | |

※1: Ripple current (100 kHz/ +45 °C), ※2: ESR (100 kHz/+20 °C) ※3: tan δ (120 Hz/+20 °C) ※4: After 5 minutes

◆ Please refer to each page in this catalog for "Reflow conditions" and "Taping specifications".

Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use.

Should a safety concern arise regarding this product, please be sure to contact us immediately.