

SAW Components

SAW Filter
TD-SCDMA 1900

Series/Type: B9483

Ordering code: B39192B9483P810

Date: January 18, 2012

Version: 2.0

EPCOS AG is a TDK Group Company.

[©] EPCOS AG 2015. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.



SAW Components B9483

SAW Filter 1900.0 MHz

Data sheet




Application

- Low-loss RF filter for mobile telephone TD-SCDMA systems.
- Unbalanced to balanced operation
- Low amplitude ripple
- Usable passband 40MHz
- Impedance 50 Ω at input and 100 Ω balanced output
- No matching network




Features

- Package size 1.4 x 1.1 x 0.4 mm³
- RoHS compatible
- Approx. weight 0.003 g
- Package for Surface Mount Technology (SMT)
- Ni, gold-plated terminals
- Electrostatic Sensitive Device (ESD)
- Moisture Sensitive Level 3



Pin configuration

1 Input unbalanced3,4 Output, balanced2,5 To be grounded





SAW Components B9483

SAW Filter 1900.0 MHz

Data sheet = MD

Characteristics

Temperature range for specification: $T = -30 \,^{\circ}\text{C}$ to +85 $^{\circ}\text{C}$

Terminating source impedance: $Z_{\rm S} = 50~\Omega$ Terminating load impedance: $Z_{\rm L} = 100~\Omega$

		min.	typ. @ 25 °C	max.	
Center frequency	f _C	_	1900.0	_	MHz
Maximum insertion attenuation 1880.0 1920.0 MH	α _{max} Hz	_	1.8	2.1	dB
Amplitude ripple (p-p) 1880.0 1920.0 MH	Δα Hz	_	0.6	1.0	dB
Input VSWR 1880.0 1920.0 MH	Hz	_	1.8	2.1	
Output VSWR 1880.0 1920.0 MH	Hz	_	1.8	2.1	
Common mode rejection ratio 1880.0 1920.0 MH	Hz	20	23	_	dB
Attenuation	α				
0.1 1795.0 MF	Ηz	30	40	_	dB
1795.0 1820.0 MH		25	32	_	dB
1820.0 1850.0 MH		20	23	_	dB
1950.0 1980.0 MH		17	20	_	dB
1980.0 2025.0 MH		15	25	_	dB
2025.0 6000.0 MH	Ηz	25	31		dB



SAW Components		B9483
SAW Filter		1900.0 MHz
Data sheet	SMD	

Maximum ratings


Operable temperature range	Т	-40/+85	°C	
Storage temperature range	T_{stg}	-40/+85	°C	
DC voltage	V_{DC}	3	V	
ESD voltage	V_{ESD}	50 ¹⁾	V	machine model, 1 pulse
Input Power at				
1880.01920.0MHz	P_{IN}	12	dBm	continuous wave

¹⁾ acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.






Transfer function (narrowband)



Transfer function (wideband)





SAW Components


SAW Filter


Data sheet

B9483

1900.0 MHz

S₁₁ function







SAW Components		B9483
SAW Filter		1900.0 MHz
Data sheet	SMD	

References

Туре	B9483
Ordering code	B39192B9483P810
Marking and package	C61157-A8-A14
Packaging	F61074-V8237-Z000
Date codes	L_1126
S-parameters	B9483_NB.s3p, B9483_WB.s3p see file header for port/pin assignment table
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for cer- tain hazardous substances in electrical and electronic equipment."
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.
Matching coilss	See Inductor pdf-catalog http://www.tdk.co.jp/tefe02/coil.htm#aname1 and Data Library for circuit simulation http://www.tdk.co.jp/etvcl/index.htm

For further information please contact your local EPCOS sales office or visit our webpage at $\underline{www.epcos.com}$.

Published by EPCOS AG Systems, Acoustics, Waves Business Group P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2012. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.



Important notes

The following applies to all products named in this publication:

- Some parts of this publication contain statements about the suitability of our products for certain areas of application. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
- We also point out that in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
- 3. The warnings, cautions and product-specific notes must be observed.
- 4. In order to satisfy certain technical requirements, some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous). Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
- 5. We constantly strive to improve our products. Consequently, the products described in this publication may change from time to time. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also reserve the right to discontinue production and delivery of products. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
- Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI).
- 7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are trademarks registered or pending in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.