



SAW Components

SAW Rx 2in1 Filter

Cellular + PCS / WCDMA Band V + WCDMA Band II

Series/type:	B9519
Ordering code:	B39202B9519P810
Date:	September 01, 2011
Version:	2.0




Application

- Low-loss 2in1 RF filter for mobile telephone CDMA systems, receive path (Rx) of Cellular and PCS
- Also applicable for mobile phone WCDMA systems, receive path of Band V and Band II
- Bandwidth:
 - Filter 1 (Cellular): 25 MHz
 - Filter 2 (PCS): 60 MHz
- Impedance transformation from:
 - Filter 1 (Cellular): 50 Ω to 100 Ω
 - Filter 2 (PCS): 50 Ω to 100 Ω
- Unbalanced to balanced operation




Features

- Package size 1.8 x 1.4 x 0.68 mm³
- RoHS compatible
- Approx. weight 0.006g
- Package for Surface Mount Technology (SMT)
- Ni, gold-plated terminals
- **RoHS compatible**
- **Electrostatic Sensitive Device (ESD)**
- **Moisture Sensitive Level 3**



Pin configuration

- 1 Input [Filter 1: Cellular]
- 4 Input [Filter 2: PCS]
- 6,7 Output [Filter 2: PCS]
- 8,9 Output [Filter 1: Cellular]
- 2,3,5,10 Ground





Data sheet



Characteristics of filter 1 (Cellular)

Temperature range for specification: $T = -30$ to $+85$ °C
 Terminating source impedance: $Z_S = 50 \Omega$ (unbalanced)
 Terminating load impedance: $Z_L = 100 \Omega$ (balanced)

		min.	typ. @ 25 °C	max.	
Center frequency	f_C	—	881.5	—	MHz
Maximum insertion attenuation	α_{max}				
869.0 ... 894.0 MHz		—	1.7	2.3	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
869.0 ... 894.0 MHz		—	0.5	1.3	dB
Amplitude ripple over any 5MHz channel	$\Delta\alpha$				
869.0 ... 894.0 MHz		—	0.6	1.0	dB
Group delay ripple over any 5MHz channel					
869.0 ... 894.0 MHz		—	13	40	ns
Input VSWR					
869.0 ... 894.0 MHz		—	1.8	2.1	
Output VSWR					
869.0 ... 894.0 MHz		—	1.8	2.2	
CMRR ($S_{21}-S_{31} / S_{21}+S_{31}$)					
869.0 ... 894.0 MHz		18	21	—	dB
Attenuation	α				
0.0 ... 820.0 MHz		47	58	—	dB
820.0 ... 835.0 MHz		43	57	—	dB
835.0 ... 849.0 MHz		44	50	—	dB
914.0 ... 950.0 MHz		24	28	—	dB
950.0 ... 1500.0 MHz		45	50	—	dB
1500.0 ... 2000.0 MHz		38	44	—	dB
2000.0 ... 3000.0 MHz		32	36	—	dB
3000.0 ... 6000.0 MHz		24	29	—	dB



SAW Components

B9519

SAW Rx 2in1 Filter

881.5 / 1960.0 MHz

Data sheet




Maximum ratings of filter 1

Operable temperature range	T	-40/+85	°C	
Storage temperature range	T _{stg}	-40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	100 ¹⁾	V	machine model, 1 pulse
Input Power at WCDMA Band V	P _{IN}	10	dBm	continuous wave @ +55 °C ambient
Tx band				


¹⁾ acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.





Transfer function (narrow band)





Transfer function (wide band)



S₁₁ function



S₂₂ function





Data sheet



Characteristics of filter 2 (PCS)

Temperature range for specification: $T = -30$ to $+85$ °C
 Terminating source impedance: $Z_S = 50 \Omega$ (unbalanced)
 Terminating load impedance: $Z_L = 100 \Omega \parallel 13nH$ (balanced)

		min.	typ. @ 25 °C	max.	
Center frequency	f_C	—	1960.0	—	MHz
Maximum insertion attenuation	α_{max}				
1930.6 ... 1989.4 MHz		—	1.9	2.6	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
1930.6 ... 1989.4 MHz		—	0.8	1.6	dB
Amplitude ripple over any 5MHz channel	$\Delta\alpha$				
1930.6 ... 1989.4 MHz		—	0.4	0.9	dB
Group delay ripple over any 5MHz channel					
1930.6 ... 1989.4 MHz		—	15	30	ns
Input VSWR					
1930.6 ... 1989.4 MHz		—	1.6	2.1	dB
Output VSWR					
1930.6 ... 1989.4 MHz		—	1.6	2.1	dB
CMRR ($S_{21}-S_{31} / S_{21}+S_{31}$)					
1930.6 ... 1989.4 MHz		16	18	—	dB
Attenuation	α				
0.0 ... 1000.0 MHz		40	48	—	dB
1000.0 ... 1600.0 MHz		34	37	—	dB
1600.0 ... 1850.0 MHz		29	32	—	dB
1850.0 ... 1910.0 MHz		20	25	—	dB
2040.0 ... 2200.0 MHz		23	33	—	dB
2200.0 ... 2590.0 MHz		30	34	—	dB
2590.0 ... 2800.0 MHz		25	31	—	dB
2800.0 ... 3400.0 MHz		25	30	—	dB
3400.0 ... 6000.0 MHz		20	28	—	dB



SAW Components

B9519

SAW Rx 2in1 Filter

881.5 / 1960.0 MHz

Data sheet



Maximum ratings of filter 2

Operable temperature range	T	-40/+85	°C	
Storage temperature range	T _{stg}	-40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	50 ¹⁾	V	machine model, 1 pulse
Input Power at WCDMA Band II	P _{IN}	10	dBm	continuous wave, @ +55 °C ambient
Tx band				


¹⁾ acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.




Data sheet





Transfer function (narrow band)





Transfer function (wide band)



S₁₁ function



S₂₂ function





SAW Components **B9519**

SAW Rx 2in1 Filter **881.5 / 1960.0 MHz**

Data sheet



References

Type	B9519
Ordering code	B39202B9519P810
Marking and package	C61157-A7-A152
Packaging	F61074-V8226-Z000
Date codes	L_1126
S-parameters	Cellular: B9519_LB_NB.s3p, B9519_LB_WB.s3p PCS: B9519_UB_NB.s3p, B9519_UB_WB.s3p See file header for port/pin assignment table.
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.
Matching coils	See http://www.tdk.co.jp/tefe02/coil.htm#aname1 http://www.tdk.co.jp/etvcl/index.htm for a large variety of matching coils.

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG
Systems, Acoustics, Waves Business Group
P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2011. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.