





FIG 1 -S: SINGLE ENDED (FJH-10-S-XX.XX-4 SHOWN) (HAND BUILT)

| TABLE | 1 | |
|------------------|-------|-------|
| No. OF POSITIONS | "A" | "B" |
| -06 | 3.50 | 2.50 |
| -10 | 5.50 | 4.50 |
| -15 | 8.00 | 7.00 |
| -20 | 10.50 | 9.50 |
| -24 | 12.50 | 11.50 |
| -25 | 13.00 | 12.00 |
| -30 | 15.50 | 14.50 |
| -40 | 20.50 | 19.50 |
| -43 | 22.00 | 21.00 |
| -50 | 25.50 | 24.50 |

NOTE:

- 1. © REPRESENTS A CRITICAL DIMENSION.
- 2. TO BE MEASURED AT BASE OF EXPOSED LEAD.
 3. ENGLISH IS PRIMARY FOR THIS MEASUREMENT.
- 4. TO BE MEASURED ON BOTH EDGES OF CABLE.

| ı | UNLESS OTHERWISE SPECIFIED, |
|---|-------------------------------------------------------------|
| | UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETER |
| | TOLERANCES ARE: |
| ı | DECIMALS ANGLES |

X.X: ±0.3 X.XX: ±0.05 X.XXX: ±0.025

MATERIAL:

PROPRIETARY NOTE THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC

DO NOT SCALE DRAWING SHEET SCALE: 6:1

CONDUCTORS: TIN PLATED COPPER SURFACE FINISH EITHER BRIGHT TIN (99.9% SN) OR MATTE TIN (95.5% SN, 3.5% AG, 1% CU) INSULATION & STIFFENER: POLYESTER

F:\DWG\MISC\MKTG\FJH-XX-X-XX.XX-X-MKT.SLDDRW



520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

DESCRIPTION

.5mm FLEX CABLE JUMPER

DWG. NO.

FJH-XX-X-XX.XX-X

BY: KEVIN B

6/28/00

SHEET 1 OF 3



