



TACTILE SWITCHES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

FSM2JSMATR=ON T/R

[Alcoswitch](#) | [FSMJMSA](#)

FSM2JSMATR

TE Internal Number: 3-1437565-0

Always EU RoHS/ELV Compliant

Actuator Style **Round**

Operating Function **No**

Contact Base Material **Copper Alloy**

Contact Plating **Silver**

Dust Proof **No**

Product Drawings

[MICRO MINIATURE PUSHBUTTON SWITCH FSM JSM](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[SWITCHES_CORE_PROGRAM_CATALOG](#)

PDF
English

[Products For Mobile Equipment](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_3-1437565-0_05042014235_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Dust Proof	No
Leg Style	Gull Wing
Illuminated	No
Product Type	Switch

Configuration Features	Operating Function	No
	Support Bracket	Without
	Configuration (Pole-Throw)	Single Pole - Single Throw
	Number of Actuators	1
	ESD Grounding Terminal	Without
	Ganged	With
	Tactile	Yes
	Snap Action	Without
Tactile Feel	With	

Body Features	Actuator Color	Gray
	Bushing Style	Unthreaded
	Actuator Material	PPS
	Actuator Force	160 g [5.648 oz]
	Actuator Profile	Extended
	Case Color	Brown
	Cover Material	Steel
	Case Material	Polyamide

Contact Features	Contact Base Material	Copper Alloy
	Contact Plating	Silver
	Contact Current Rating (mA)	50

Termination Features	Termination Type	Printed Circuit Board
----------------------	------------------	------------------------------

Mechanical Attachment	Mounting Type	Surface Mount
	Mounting Angle	Vertical

Housing Features	Low Profile	With
	Process Sealed	No

Dimensions	Actuator Length	.7 mm [.028 in]
	Switch Height	4.3 mm [.169 in]
	Button Width	3.5 mm [.138 in]
<hr/>		
Usage Conditions	Temperature Rating (°C)	Standard
<hr/>		
Packaging Features	Packaging Method	Tape & Reel
<hr/>		
Other	Comment	(On) indicates momentary position.
<hr/>		
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	