



RELAYS, CONTACTORS & SWITCHES

TACTILE SWITCHES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

FSM4JSMATR=TACT SWITCH 6X6MIL

Alcoswitch | FSMJSMA

FSM4JSMATR

TE Internal Number: 4-1437565-2

Always EU RoHS/ELV Compliant

Actuator Style **Round**

Operating Function **No**

Contact Base Material **Copper Alloy**

Contact Plating **Silver**

Dust Proof **No**



Product Drawings

[MICRO MINIATURE PUSHBUTTON SWITCH FSM JSM](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[SWITCHES_CORE_PROGRAM_CATALOG](#)

PDF
English

[Products For Mobile Equipment](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_4-1437565-2_062920142347_dmtec](#)
 PDF
 English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Actuator Style	Round
	Dust Proof	No
	Leg Style	Gull Wing
	Illuminated	No
	Product Type	Switch
Configuration Features	Operating Function	No
	Support Bracket	Without
	Configuration (Pole-Throw)	Single Pole - Single Throw
	Number of Actuators	1
	ESD Grounding Terminal	Without
	Ganged	With
	Tactile	Yes
	Snap Action	Without
	Tactile Feel	With
Body Features	Actuator Color	Black
	Bushing Style	Unthreaded
	Actuator Material	Polyamide
	Actuator Force	160 g [5.648 oz]
	Actuator Profile	Extended
	Case Color	Brown
	Cover Material	Steel
	Case Material	Polyamide
Contact Features	Contact Base Material	Copper Alloy
	Contact Plating	Silver
	Contact Current Rating (mA)	50

Termination Features	Termination Type	Printed Circuit Board
Mechanical Attachment	Mounting Type	Surface Mount
	Mounting Angle	Vertical
Housing Features	Low Profile	With
	Process Sealed	No
Dimensions	Actuator Length	1.4 mm [.055 in]
	Switch Height	5 mm [.196 in]
	Button Width	3.5 mm [.138 in]
Usage Conditions	Temperature Rating (°C)	Standard
Packaging Features	Packaging Method	Tape & Reel
Other	Comment	(On) indicates momentary position.

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

