



TACTILE SWITCHES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

FSM6JSMA=SMT,TACTILE,PB SWITCH

Alcoswitch | FSMJSMA

FSM6JSMA

TE Internal Number: 4-1437565-9

Always EU RoHS/ELV Compliant

Actuator Style **Round**

Operating Function **No**

Contact Base Material **Copper Alloy**

Contact Plating **Silver**

Dust Proof **No**

Product Drawings

MICRO MINIATURE PUSHBUTTON SWITCH FSM JSM

PDF
English

CAD Files

Customer View Model

2D_DXF.ZIP
English

3D PDF

PDF
3D

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Catalog Pages/Data Sheets

SWITCHES_CORE_PROGRAM_CATALOG

PDF
English

Products For Mobile Equipment

PDF
English

Product Environmental Compliance

TE Material Declaration

MD_4-1437565-9_051920142155_dmtec

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Dust Proof	No
Leg Style	Gull Wing
Illuminated	No
Product Type	Switch

Configuration Features	Operating Function	No
	Support Bracket	Without
	Configuration (Pole-Throw)	Single Pole - Single Throw
	Number of Actuators	1
	ESD Grounding Terminal	Without
	Ganged	With
	Tactile	Yes
	Snap Action	Without
Tactile Feel	With	

Body Features	Actuator Color	Black
	Bushing Style	Unthreaded
	Actuator Material	Polyamide
	Actuator Force	160 g [5.648 oz]
	Actuator Profile	Extended
	Case Color	Brown
	Cover Material	Steel
	Case Material	Polyamide

Contact Features	Contact Base Material	Copper Alloy
	Contact Plating	Silver
	Contact Current Rating (mA)	50





Termination Features	Termination Type	Printed Circuit Board
----------------------	------------------	------------------------------

Mechanical Attachment	Mounting Type	Surface Mount
	Mounting Angle	Vertical

Housing Features	Low Profile	With
	Process Sealed	No

Dimensions	Actuator Length	3.4 mm [.134 in]
	Switch Height	7 mm [.276 in]
	Button Width	3.5 mm [.138 in]
Usage Conditions	Temperature Rating (°C)	Standard
Packaging Features	Packaging Method	Loose Piece
Other	Comment	(On) indicates momentary position.
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

CRIMP QUICK DISCONNECTS	SURFACE MOUNT RESISTORS	TACTILE SWITCHES	THROUGH-HOLE RESISTORS
 <p>187 FAST REC 24-20 .0126TPBR 62181-1</p> <p>Save to List Find Similar Products</p>	 <p>CRGH0805 1% 220R 0.33W CRGH0805F220R</p> <p>Save to List Find Similar Products</p>	 <p>FSM2JRT=PUSHBUTTON S SWITCH FSM2JRT</p> <p>Save to List Find Similar Products</p>	 <p>CFR16 5% 390K CFR16J390K</p> <p>Save to List Find Similar Products</p>