



TACTILE SWITCHES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

FSMCTATR=TACTILE SWITCH T&R

Alcoswitch | FSMCT

8-1437565-1

TE Internal Number: 8-1437565-1

Alias ID: FSMCTA

Always EU RoHS/ELV Compliant

Actuator Style **Round**

Operating Function **No**

Contact Base Material **Copper Alloy**

Contact Plating **Silver**

Dust Proof **No**

Product Drawings

MICRO MINIATURE PUSHBUTTON SWITCH

PDF
English

CAD Files

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Customer View Model

2D_DXF.ZIP
English

3D PDF

PDF
3D

Catalog Pages/Data Sheets

Products For Mobile Equipment

PDF
English

SWITCHES_CORE_PROGRAM_CATALOG

PDF
English

Product Environmental Compliance

TE Material Declaration

MD_8-1437565-1_04042013644_dmtec





PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	Dust Proof	No
	Illuminated	No
	Leg Style	Gull Wing
	Product Type	Switch
<hr/>		
Configuration Features	Operating Function	No
	Support Bracket	Without
	Configuration (Pole-Throw)	Single Pole - Single Throw
	Number of Actuators	1
	Ganged	With
	ESD Grounding Terminal	Without
	Tactile	Yes
	Snap Action	Without
	Tactile Feel	With
<hr/>		
Body Features	Actuator Color	None
	Bushing Style	Unthreaded
	Actuator Material	Brass
	Actuator Force	260 g [9.178 oz]
	Cover Material	Nickel
	Actuator Profile	Extended
	Case Material	Nylon
	Case Color	Ivory
<hr/>		
Contact Features	Contact Base Material	Copper Alloy
	Contact Plating	Silver
	Contact Current Rating (mA)	20
<hr/>		
Termination Features	Termination Type	Printed Circuit Board
<hr/>		
Mechanical Attachment	Mounting Type	Surface Mount
	Mounting Angle	Vertical
<hr/>		
Housing Features	Low Profile	With
	Process Sealed	No
<hr/>		

Dimensions	Actuator Length	.4 mm [.016 in]
	Switch Height (in)	.059
	Button Width	1.98 mm [.078 in]
Usage Conditions	Temperature Rating (°C)	Standard
Packaging Features	Packaging Method	Tape & Reel
Other	Comment	(On) indicates momentary position.
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

STANDARD POWER RELAYS	CRIMP QUICK DISCONNECTS	USB CONNECTORS	MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES
 <p>RY211048 RY211048</p> <p>Save to List Find Similar Products</p>	 <p>250 FASTON REC 2-160256-2</p> <p>Save to List Find Similar Products</p>	 <p>REC TYPE B ASSY (Au) MICRO USB 1981568-1</p> <p>Save to List Find Similar Products</p>	 <p>2P AMPMODU II STIFT LEI 826652-2</p> <p>Save to List Find Similar Products</p>