



CONNECTOR HOUSINGS



✓ Active

↓ **PRODUCT DRAWING**
Japanese

↓ **3D PDF**

TE CONNECTIVITY (TE)

DYNAMIC D-2100 TAB HSG 3P F/H

[Dynamic Series](#) | [Dynamic 2000 Series](#)

1-1318117-3

TE Internal Number: 1-1318117-3

Always EU RoHS/ELV Compliant

Connector System **Wire-to-Wire**

Centerline **2.5 mm [.098 in]**

Number of Positions **3**

Number of Rows **1**

Housing Material **Polyester GF**

Product Drawings

[SINGLE ROW TAB HSG \(FREE HANGING\) DYNAMIC D-2100D](#)

PDF (**TIFF AVAILABLE**)

Japanese

[SINGLE ROW TAB HSG \(FREE HANGING\) DYNAMIC D-2100D](#)

PDF (**TIFF AVAILABLE**)

Japanese

CAD Files

[Customer View Model](#)

2D_DXF.ZIP

English

[3D PDF](#)

PDF

3D

[Customer View Model](#)

3D_IGS.ZIP

English

[Customer View Model](#)

3D_STP.ZIP

English

Catalog Pages/Data Sheets

[D2000 Series Dynamic Connectors](#)

PDF

English

[1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH](#)

PDF

English

Product Specifications

Product Specification

[DYNAMIC CONNECTOR D-2000 SERIES](#)

PDF

Japanese

Application Specification

[Dynamic Connector D-2000 Series](#)

TIF

Japanese

[Dynamic Connector D-2000 Series](#)

PDF

Japanese

Qualification Test Report

[DYNAMIC D-2000 SERIES CONNECTOR](#)

DYNAMIC D-2000 SERIES CONNECTORPDF
Japanese**DYNAMIC D-2000 SERIES CONNECTOR**TIF
Japanese**Product Environmental Compliance**

TE Material Declaration

[MD_1-1318117-3_06052015922_dmtec](#)PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector System	Wire-to-Wire
	Connector Style	Plug
	Sealed	No
	Applies To	Wire/Cable
	Series Number	2000
	Glow Wire Rating	Standard Part - Not Glow Wire
	Product Type	Connector
	Connector Type	Housing

Configuration Features	Number of Positions	3
	Number of Rows	1
	Selectively Loaded	No
	Preloaded	No

Electrical Characteristics	Operating Voltage	250 VAC [250 VDC]
----------------------------	-------------------	----------------------------

Body Features	Sealable	No
---------------	----------	-----------

Contact Features	Contact Type	Tab
	Contact Layout	Inline
	Shunts/Shorting Bars	Without
	Multiple Contact Types	Without

Mechanical Attachment	Panel Mount Retention	Without
-----------------------	-----------------------	----------------

Housing Features	Centerline	2.5 mm [.098 in]
	Housing Material	Polyester GF

Housing Color **Black**

Dimensions	Length	10.2 mm [.401 in]
	Height	30.69 mm [1.208 in]
	Width	9.45 mm [.372 in]
Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]





Operation/Application	Halogen Free	Yes
	For Use With	Receptacle Housing

Industry Standards	CSA Rating	Certified
	CSA File Number	LR7189
	UL Rating	Recognized
	CSA Certified	Yes
	VDE Tested	No
	UL File Number	E28476
	Agency/Standard	CSA, UL
	UL Flammability Rating	UL 94V-0

Packaging Features	Packaging Quantity	900
	Packaging Method	Bag

Product Compliance [Statement of Compliance PDF](#)
[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>I/O CONNECTOR CONTACTS</p>  <p>DYNAMIC D-2 TAB CONT M L/P 1318111-1</p> <p>Save to List Find Similar Products</p>	<p>PRO-CRIMPER & DIES</p>  <p>DIE ASSY 1762951-1</p> <p>Save to List Find Similar Products</p>	<p>RECTANGULAR CONNECTOR HOUSINGS</p>  <p>DYNAMIC 1200D TAB HSG 20P F/H 1-1903130-0</p> <p>Save to List Find Similar Products</p>	<p>I/O CONNECTOR CONTACTS</p>  <p>DYNAMIC D-3 TAB CONT. L 20-16 175286-2</p> <p>Save to List Find Similar Products</p>
--	--	--	--

Products - 4 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series I Dynamic 2000 Series

**DYNAMIC D-2 TAB
CONT M L/P - 1318111-1**

TE INTERNAL NUMBER: 1318111-1

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **250 VAC**

Contact Retention **With**

Contact Retention Type **Locking**

Lance



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series I Dynamic 2000 Series

**DYNAMIC D-2 TAB
CONT S L/P - 1318112-1**

TE INTERNAL NUMBER: 1318112-1

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **250 VAC**

Contact Retention **With**

Contact Retention Type **Locking**

Lance



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series I Dynamic 2000 Series

**DYNAMIC D-2000 TAB
CONT S - 1318110-1**

TE INTERNAL NUMBER: 1318110-1

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **250 VAC**

Contact Retention **With**



Contact Retention Type **Locking**

Lance