

QUICK DISCONNECTS













PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE) 250 FASTON IS

FASTON | FASTON Terminals and Housings

1-160304-2

TE Internal Number: 1-160304-2 Alias ID: AMP-1-0160304-2, D89496-000

Always EU RoHS/ELV Compliant

Mating Tab Width 6.35 mm [.25 in]

Mating Tab Thickness .81 mm [.032 in]

Wire Insulation Diameter 3 - 4.29 mm [.118 - .169 in]

Wire Size (AWG) 17 - 13

Wire Size (mm²) **1 – 2.5**



Product Drawings

FASTON Conn., .250 Sr. Rec. Ctc.

PDF (TIFF AVAILABLE)

English

FASTON Conn., .250 Sr. Rec. Ctc.

PDF (TIFF AVAILABLE)
English

CAD Files

3D PDF

PDF **3D**

Customer View Model

2D DXF.ZIP English

Customer View Model

3D_IGS.ZIP English

Customer View Model

3D_STP.ZIP English

Product Environmental Compliance

TE Matarial Daglaration

OFO EACTONIC

PDF **English**

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Wire Stop	No
	Disconnect Type	Quick Disconnect
	Insertion Force	Normal
	FASTON	Yes
	Wire/Cable Composition	Stranded
	Insulated	No
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Applies To	Hermetic Header Tabs
Configuration Features	Terminal Angle	Straight
	Connection Capacity	Single
Body Features	Plating Material	Brass, Tin
	Fully Insulated	Yes
Contact Features	Terminal Orientation	Straight
	Contact Plating Material	Tin
Termination Features	Crimp Type	F-Crimp
Dimensions	Mating Tab Width	6.35 mm [.25 in]
	Mating Tab Thickness	.81 mm [.032 in]
	Wire Insulation Diameter	3 – 4.29 mm [.118 – .169 in]
	Wire Size (AWG)	17 – 13
	Wire Size (mm²)	1 – 2.5
	Overall Length	20.2 mm [.795 in]
Industry Standards	UL Rating	Listed
	CSA Certified	Yes

Packaging Features Packaging Method

	Packaging Quantity	500
Other	Line	Premier
Product Compliance	Statement of Compliance	

VIEW ALL PRODUCT COMPLIANCE

Day

ı ackayıny ivietilüü

гаскаўшу геацитез

