



# RIBBON CABLE CONNECTORS



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)

## 64 NOVO MIL/CTR 30DP, LEAD FREE

AMP-LATCH | AMP-LATCH - NOVO

1-1658622-2

TE Internal Number: 1-1658622-2

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [ .1 in ]**

PCB Mount Retention **Without**

PCB Mounting Orientation **Vertical**

Termination Method to PC Board **Through Hole - Solder**

Termination Method to Wire/Cable **Insulation Displacement Crimp (IDC)**

### Product Drawings

#### RECEPTACLE ASSY, CENTER & MILITARY POLARIZATION LEAD FREE AMP-LATCH NOVO

PDF  
English

### CAD Files

#### Customer View Model

2D\_DXF.ZIP  
English

#### 3D PDF

PDF  
3D

#### Customer View Model

3D\_IGS.ZIP  
English

#### Customer View Model

3D\_STP.ZIP  
English

### Catalog Pages/Data Sheets

#### Ribbon Cable Interconnect Solutions

PDF  
English

### Product Specifications

#### Product Specification

#### Connector, Flat Cable Round Conductor, AMP-LATCH Novo Receptacles

PDF  
English

#### Application Specification

#### AMP-LATCH Novo Receptacles For Ribbon Cable With Conductors Having 1.27 Mm (.050 In.) Centerlines

PDF  
English

#### Qualification Test Report

#### Connector, Flat Cable, Round Conductor, AMP-LATCH NOVO & NOVO Stackable Receptacles

TIF  
English

#### Connector, Flat Cable, Round Conductor, AMP-LATCH NOVO & NOVO Stackable Receptacles

PDF  
English

## Product Environmental Compliance

TE Material Declaration

[MD\\_1-1658622-2\\_04222014114\\_dmtec](#)

PDF  
English

## Instruction Sheets

Instruction Sheet (U.S.)

[CONNECTOR-SPECIFIC KIT 768341-1 F/AMP-LATCH STANDARD & NOVO RECEPTACLE CONNECTORS](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

### Product Type Features

PCB Mounting Orientation	<b>Vertical</b>
Shrouded	<b>No</b>
Row-to-Row Spacing	<b>2.54 mm [ .1 in ]</b>
Connector Style	<b>Receptacle</b>
Profile	<b>Low</b>
Applies To	<b>Wire/Cable</b>
Product Type	<b>Connector</b>
Board Standoff	<b>Without</b>
Connector Type	<b>Connector Assembly</b>
Wire/Cable Type	<b>Ribbon Cable</b>
Connector System	<b>Wire-to-Board</b>
Ejection Latches	<b>Without</b>

### Configuration Features

Number of Positions	<b>64</b>
Number of Rows	<b>2</b>

### Electrical Characteristics

UL Voltage Rating (VAC)	<b>250</b>
Operating Voltage (VAC)	<b>250</b>
Insulation Resistance (M $\Omega$ )	<b>5000</b>

### Body Features





Header Type	<b>Pin Header</b>
Daisy Chain	<b>Without</b>

### Contact Features

Contact Mating Area Plating Material	<b>Gold or Palladium Nickel or Performance Based</b>
Contact Mating Area Plating Thickness	<b>.76 <math>\mu</math>m [ 29.92 <math>\mu</math>in ]</b>
Contact Design	<b>Tuning Fork</b>

	Contact Transmits (Typical)	<b>Signal (Data)</b>
	Contact Current Rating (A)	<b>1</b>
	Contact Base Material	<b>Phosphor Bronze</b>
	Contact Type	<b>Socket</b>
	Contact Termination Area Plating Material	<b>Tin</b>
	Contact Termination Area Plating Thickness	<b>1.27 <math>\mu\text{m}</math> [ 50 <math>\mu\text{in}</math> ]</b>
Termination Features	Termination Method to PC Board	<b>Through Hole - Solder</b>
	Termination Method to Wire/Cable	<b>Insulation Displacement Crimp (IDC)</b>
Mechanical Attachment	PCB Mount Retention	<b>Without</b>
	Mating Alignment Type	<b>Polarization</b>
	Mating Alignment	<b>With</b>
	Polarization	<b>With</b>
	Panel Mount Retention	<b>Without</b>
	PCB Mount Alignment	<b>Without</b>
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Color	<b>Black</b>
	Housing Material	<b>Thermoplastic</b>
Dimensions	Height	<b>15.16 mm [ .5968 in ]</b>
	Accepts Wire Insulation Diameter Range	<b>.787 – .94 mm [ .031 – .037 in ]</b>
	Length	<b>85.85 mm [ 3.3799 in ]</b>
	Width	<b>7.49 mm [ .2949 in ]</b>
	Wire/Cable Size	<b>.08 – .15 mm<sup>2</sup>, 158 – 296 CMA, 28 – 26 AWG</b>
Usage Conditions	Operating Temperature Range	<b>-65 – 105 °C [ -85 – 221 °F ]</b>
Industry Standards	CSA File Number	<b>LR 7189</b>
	UL Flammability Rating	<b>UL 94V-0</b>
	Agency/Standard	<b>CSA, UL</b>
	UL Rating	<b>Recognized</b>
	UL File Number	<b>E28476</b>
Packaging Features	Packaging Method	<b>Tube, Tube/Box</b>
	Packaging Quantity	<b>50</b>

## CUSTOMERS ALSO BOUGHT

<p>RIBBON CONNECTOR ACCESSORIES</p>  <p>064 STRAIN RELIEF A-L RCPT 1-499252-3</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p>RIBBON CABLE CONNECTORS</p>  <p>60 NOVO MIL/CTR 15DP, LEAD FREE 1-1658621-1</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p>RIBBON CONNECTOR ACCESSORIES</p>  <p>060 STRAIN RELIEF A-L RCPT 499252-7</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p>RIBBON CABLE CONNECTORS</p>  <p>AMP-LATCH UNV HDR, 20 POSN, VERT 1658694-1</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>
--	---	--	--

Products - 31 Results

[View All](#)

[Compare 0/10](#)

Relation Type

RELATIONSHIP

### Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors  
AMP-LATCH | Universal Headers

**A/L UNIV HDR 64P RA  
SHT LAT BLUE**  
- 3-5499345-2

TE INTERNAL NUMBER: 3-5499345-2

[Active](#)

Always EU RoHS/ELV Compliant

Centerline **2.54 mm**

PCB Mount Retention **Without**

PCB Mounting Orientation **Right Angle**

Termination Method to PC Board **Through Hole**

Shrouded **Yes**

RELATIONSHIP

### Mating Products

Used to identify Mating Parts


[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors  
AMP-LATCH | AMP-LATCH

Always EU RoHS/ELV Compliant



## 064 UNIV I/O 30DP NO EARS LTCH - 2-111504-6

TE INTERNAL NUMBER: 2-111504-6

✓ Active

Centerline **2.54 mm**

PCB Mount Retention **Without**

Termination Method to

Wire/Cable **Insulation**

**Displacement Crimp (IDC)**

Shrouded **Yes**

Row-to-Row Spacing **2.54 mm**

### PRODUCT - MATING PRODUCTS



Connectors - Ribbon Connector Accessories  
AMP-LATCH | AMP-LATCH - NOVO

## 064 STRAIN RELIEF A-L RCPT - 1-499252-3

TE INTERNAL NUMBER: 1-499252-3  
ALIAS ID: 2-42935-7202

✓ Active

Always EU RoHS/ELV Compliant

Accessory Type **Strain Relief**

### RELATIONSHIP

## Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

### PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors  
AMP-LATCH | Universal Headers

## A/L UNIV HDR 64P RA HT - 1-5111105-2

TE INTERNAL NUMBER: 1-5111105-2

✓ Active

Always EU RoHS/ELV Compliant

Centerline **2.54 mm**

PCB Mount Retention **Without**

PCB Mounting Orientation **Right Angle**

Termination Method to PC Board  
**Through Hole (SMT Compatible)**

Shrouded **Yes**

### PRODUCT - MATING PRODUCTS



Connectors - Ribbon Connector Accessories  
AMP-LATCH | AMP-LATCH - NOVO

## 064 STRAIN RELIEF A-L RCPT - 1-499252-3

TE INTERNAL NUMBER: 1-499252-3  
ALIAS ID: 2-42935-7202

✓ Active

Always EU RoHS/ELV Compliant

Accessory Type **Strain Relief**