



# 1-1718646-1 Product Details

[Share](#) | [Print](#) | [Email](#)


**1-1718646-1**

TE Internal Number: 1-1718646-1

Active

[View 3D PDF](#)

## Multiple Contact Point (MCP) & MCON Contact Systems

Always EU RoHS/ELV Compliant (Statement of Compliance)

### Product Highlights:

- MCON Product Line
- Wire-to-Wire
- Applies To Wire/Cable
- Connector
- Housing

[View all Features](#)

### Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)
[Request Sample](#)
[Find Similar Products](#)
[Buy Product](#)

## Documentation & Additional Information

### Product Drawings:

- [CONNECTOR, 6POS., AMP MCP 1.2, SEALED Gehaeuse, 6pol...](#) (PDF, English)

### Catalog Pages/Data Sheets:

- None Available

### Product Specifications:

- None Available

### Application Specifications:

- None Available

### Instruction Sheets:

- None Available

### CAD Files: (CAD Format & Compression Information)

- [2D Drawing](#) (DXF, Version E)
- [3D Model](#) (IGES, Version E)
- [3D Model](#) (STEP, Version E)

### Related Products:

- [Tooling](#)

[List all Documents](#)

## Product Features (Please use the Product Drawing for all design activity)

### Product Type Features:

- Product Line = MCON
- Product Type = Connector
- Connector Type = Housing
- [Wire/Cable Type](#) = FLR (Thin Walled Cable)
- Key Type = Standard
- Sealed = Yes

### Mechanical Attachment:

- Contact Retention = With
- Contact Retention Type = Retainer
- Mating Retention Type = Connector Position Assurance (CPA)

### Termination Features:

- Termination Method to Wire/Cable = Crimp
- Seal Type = Peripheral

### Dimensions:

- Mating Area Interface Dimensions (mm [in]) = 1.20 [.047]

### Body Features:

- Cable Exit Angle = 180°
- Mating Retention = With
- Wire Type = Stranded
- Seal Material = Silicone
- Seal Color = Natural
- Used With = Tab Housing

### Contact Features:

### Configuration Features:

- Number of Positions = 6
- Number of Rows = 1

### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

### Identification Marking:

- Keying = A

### Environmental:

- Operating Temperature (°C [°F]) = -40 - +130 [-40 - +266]

### Conditions for Usage:

- Applies To = Wire/Cable

### Operation/Application:

- Application Use = Wire-to-Wire

### Packaging Features:

- Packaging Method = Box/Carton
- Packaging Quantity = 1,000

### Other:

- Brand = TE Connectivity
- Comment = Degree of Protection: IPIP X 4K / X 9K

Feedback

- Contact Type = Socket

**Housing Features:**

- Connector Style = Receptacle
- Housing Material = PA6 - GF15
- Housing Color = Black
- Mating Alignment = With
- Mating Alignment Type = Keyed

**Corporate Information**

[About TE](#)  
[Investors](#)  
[News Room](#)  
[Supplier Portal](#)  
[Careers](#)  
[Terms & Conditions](#)  
[Privacy Policy](#)  
[AODA Accessibility Policy](#)  
[AODA Multi-Year Accessibility Plan](#)

**Quick Links**

[Distributor Inventory](#)  
[Product Cross Reference](#)  
[Documents & Drawings](#)  
[Product Compliance Support Center](#)  
[Site Map](#)

**Customer Support**

[Email or Chat With Us](#)  
[Find a Phone Number](#)  
[Knowledge Base](#)  
[Manage Your Account](#)

**Keep Me Informed**