

PCI & PCI EXPRESS CONNECTORS





✓ Activ



PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

PCI Express RA assy 5.8mm slot 3.1mm pc

1-1761465-4

TE Internal Number: 1-1761465-4

Always EU RoHS/ELV Compliant

Number of Positions 164

Centerline 1 mm [.039 in]

Termination Post Length 3.1 mm [.122 in]

Contact Mating Area Plating Thickness (μ in) 30

PCB Mounting Orientation Right Angle

Product Drawings

PCI EXPRESS CARD EDGE CONNECTOR ASSEMBLY RIGHT ANGLE, 5.8mm SLOT

HEIGHT THROUGH PDF (TIFF AVAILABLE)

English

PCI EXPRESS CARD EDGE CONNECTOR ASSEMBLY RIGHT ANGLE, 5.8mm SLOT

HEIGHT THROUGH PDF (TIFF AVAILABLE)

English

CAD Files Customer View Model

3D_STP.ZIP **English**

Customer View Model

2D_DXF.ZIP **English**

3D PDF

PDF

Customer View Model

3D_IGS.ZIP English

Catalog Pages/Data Sheets 4-1773442-7 Card Edge Connector For PCI Express Applications

PDF **English**

Product Environmental Compliance

TE Material Declaration MD_1-1761465-4_0325201332_dmtec

PDF English

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	Right Angle
	Ejector	Without
	Bus Type	PCI Express
	Type of Connector	Card Edge
	Product Type	Connector
Configuration Features	Number of Positions	164
	Number of Pylons	2
Electrical Characteristics	Operating Voltage (VAC)	50
	Current Rating (A)	1.1
	Voltage (VAC)	50
Body Features	Weight (g)	21.302
	Pylon Material	Plastic
Contact Features	Contact Mating Area Plating Thickness (µin)	30
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Material	Gold
Termination Features	Termination Post Length	3.1 mm [.122 in]
Mechanical Attachment	PCB Mounting Style	Through Hole
Housing Features	Centerline	1 mm [.039 in]
	Housing Color	Black
	Housing Material	High Temperature Thermoplastic
Dimensions	Height	9.4 mm [.37 in]
	Width	19.6 mm [.772 in]
	PCB Thickness (Accepted)	1.57 mm [.062 in]
	Length	89 mm [3.504 in]
Usage Conditions	Operating Temperature Range (°C)	-40 – 85
Operation/Application	Pick and Place Cover	Without

1.1

Packaging Features	Packaging Quantity Packaging Method	50 Tray, Tray/Box
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	