



CONNECTORS

## CONNECTOR HOUSINGS



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### DYNAMIC 3200 REC HSG 4P SGL

[Dynamic Series](#) | [Dynamic 3000 Series](#)

1-178128-4

TE Internal Number: 1-178128-4

[Always EU RoHS/ELV Compliant](#)

Connector System **Wire-to-Board, Wire-to-Wire**

Insertion Force **9.8 Newton**

Centerline **5.08 mm [ .2 in ]**

Number of Positions **4**

Number of Rows **1**



#### Product Drawings

[DYNAMIC D-3200, 5.08 PITCH RECEPTACLE HOUSING \(KEY:X,Y\)](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

#### Catalog Pages/Data Sheets

[D3000 Series Dynamic Connectors Continued](#)

PDF  
English

[1-1773732-4\\_DYNAMICSERIES\\_CATALOG\\_ENGLISH](#)

PDF  
English

## Product Specifications

Product Specification	<a href="#">Dynamic Connector D-3000 Series</a> TIF Japanese
Qualification Test Report	<a href="#">Dynamic Connector D-3000 Series</a> PDF Japanese
	<a href="#">DYNATAP CONNECTOR D-3200</a> PDF Japanese
	<a href="#">DYNATAP CONNECTOR D-3200</a> TIF Japanese

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector System	<b>Wire-to-Board, Wire-to-Wire</b>
	Insertion Force	<b>9.8 Newton</b>
	Connector Style	<b>Receptacle</b>
	Sealed	<b>No</b>
	Applies To	<b>Printed Circuit Board, Wire/Cable</b>
	Series Number	<b>3000</b>
	Glow Wire Rating	<b>Standard Part - Not Glow Wire</b>
	Product Type	<b>Connector</b>
	Connector Type	<b>Housing</b>

Configuration Features	Number of Positions	<b>4</b>
	Number of Rows	<b>1</b>
	Selectively Loaded	<b>No</b>
	Preloaded	<b>No</b>

Electrical Characteristics	Operating Voltage	<b>600 VAC [ 600 VDC ]</b>
----------------------------	-------------------	----------------------------

Body Features	Sealable	<b>No</b>
---------------	----------	-----------

Contact Features	Contact Type	<b>Socket</b>
	Contact Layout	<b>Inline</b>
	Shunts/Shorting Bars	<b>Without</b>
	Multiple Contact Types	<b>Without</b>

Mechanical Attachment	Panel Mount Retention	<b>Without</b>
-----------------------	-----------------------	----------------

Housing Features	Centerline	<b>5.08 mm [ .2 in ]</b>
	Housing Material	<b>Polyester GF</b>
	Housing Color	<b>Black</b>
Dimensions	Length	<b>34.78 mm [ 1.36 in ]</b>
	Height	<b>22.8 mm [ .897 in ]</b>
	Width (mm)	<b>7.15</b>
Usage Conditions	Operating Temperature Range	<b>-55 – 105 °C [ -67 – 221 °F ]</b>
Operation/Application	Halogen Free	<b>Yes</b>
	For Use With	<b>Plug Housing &amp; Header</b>
Industry Standards	CSA Rating	<b>Certified</b>
	CSA File Number	<b>LR7189</b>
	UL Rating	<b>Recognized</b>
	CSA Certified	<b>Yes</b>
	VDE Tested	<b>No</b>
	UL File Number	<b>E28476</b>
	Agency/Standard	<b>CSA, UL</b>
	UL Flammability Rating	<b>UL 94V-0</b>
Packaging Features	Packaging Quantity	<b>250</b>
	Packaging Method	<b>Bag</b>
Product Compliance	<p><a href="#">Statement of Compliance</a> PDF</p> <p><a href="#">VIEW ALL PRODUCT COMPLIANCE</a></p>	



