



STANDARD RECTANGULAR CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

DYNAMIC 3100 HDR V 3P ASSY

[Dynamic Series](#) | [Dynamic 3000 Series](#)

1-178313-2

TE Internal Number: 1-178313-2

Always EU RoHS/ELV Compliant

Product Type **Connector**

Mating Alignment **With**

Mating Alignment Type **Keyed**

Mating Retention **With**

Mating Retention Type **Latch**

Product Drawings

[3 Pos Single Row Vertical Hdr Assy For Dynamic D-3100](#)

PDF (**TIFF AVAILABLE**)
English

[3 Pos Single Row Vertical Hdr Assy For Dynamic D-3100](#)

PDF (**TIFF AVAILABLE**)
English

CAD Files

[3D PDF](#)

PDF
English

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[D3000 Series Dynamic Connectors](#)

PDF
English

[1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH](#)

PDF
English

Product Specifications

Product Specification

[Dynamic Connector D-3000 Series](#)

TIF
Japanese

[Dynamic Connector D-3000 Series](#)

PDF
Japanese

Qualification Test Report

[DYNAMIC D-3000 SERIES CONNECTOR](#)

PDF
Japanese

Product Environmental Compliance

TE Material Declaration

[MD_1-178313-2_121120151147_dmtc](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Connector
	PCB Mounting Orientation	Vertical
	Sealed	No
	Connector System	Wire-to-Board
	Shielded	No
	Insertion Force	Standard
	Row-to-Row Spacing	7.62 mm [.299 in]
	Connector Style	Plug
	Glow Wire Rating	Standard Part - Not Glow Wire
	Strain Relief	Without
	Series Number	3000
	Shrouded	Yes
	Connector Type	Header
	Applies To	Printed Circuit Board

Configuration Features	Number of Positions	3
	Number of Rows	1
	Preloaded	Yes
	Keying	X
	Selectively Loaded	No

Electrical Characteristics	Operating Voltage	250 VAC [250 VDC]
	UL Voltage Rating	250 VAC [250 VDC]

Body Features	Header Type	Shrouded
	Sealable	No

Contact Features	Contact Plating Material	Gold
	Contact Current Rating (A)	12
	Contact Style	Straight

Contact Style	Through Hole
Contact Transmits (Typical)	Power, Signal (Data)
Shunts/Shorting Bars	Without
Contact Layout	Inline
Tail Plating Thickness	2 µm [78.74 µin]
Multiple Contact Types	Without
Contact Type	Tab
Tail Plating Material	Tin

Termination Features	Termination Method to PC Board	Through Hole - Solder
----------------------	--------------------------------	------------------------------

Mechanical Attachment	Mating Alignment	With
	Mating Alignment Type	Keyed
	Mating Retention	With
	Mating Retention Type	Latch
	PCB Mount Retention	With
	PCB Mount Retention Type	Retention Leg
	Contact Retention	Without
	PCB Mount Alignment	Without
	Lock Type	Latch

Housing Features	Centerline	3.81 mm [.149 in]
	Housing Material	Polyester GF
	Housing Color	Black

Dimensions	PCB Thickness (Recommended)	1.6 mm [.063 in]
	Tail Length	3.8 mm [.149 in]
	Width	9.35 mm [.368 in]
	Length	21.62 mm [.851 in]
	Height	21.6 mm [.85 in]

Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
------------------	-----------------------------	--------------------------------------

Operation/Application	Assembly Integration Feature	Without
	Halogen Free	Yes
	For Use With	Receptacle Housing

Industry Standards	UL Flammability Rating	UL 94V-0
	CSA File Number	LR7189
	VDE Tested	No
	CSA Rating	Certified
	UL Rating	Recognized
	Agency/Standard	CSA, UL
	UL File Number	E28476





Packaging Features	Packaging Quantity	23
	Packaging Method	Tube, Tube/Box

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>STANDARD RECTANGULAR CONNECTORS</p>  <p>DYNAMIC 3100 HDR H 3P ASSY 1-178293-5</p> <p>Save to List</p> <p>Find Similar Products</p>	<p>RECTANGULAR POWER CONNECTORS</p>  <p>15P UMNL HDR ASSY PC 94VO LF 350830-4</p> <p>Save to List</p> <p>Find Similar Products</p>	<p>RECTANGULAR POWER CONNECTORS</p>  <p>12P UMNL HDR ASSY PC 94VO LF 350829-4</p> <p>Save to List</p> <p>Find Similar Products</p>	<p>STANDARD RECTANGULAR CONNECTORS</p>  <p>DYNAMIC 3100 HDR 4P ASSY V K/X 1-178314-2</p> <p>Save to List</p> <p>Find Similar Products</p>
---	--	--	---