



CONNECTOR HOUSINGS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

DYNAMIC D-3200S TAB HSG 2P K/X

[Dynamic Series](#) | [Dynamic 3000 Series](#)

1-179552-2

TE Internal Number: 1-179552-2

Always EU RoHS/ELV Compliant

Connector System **Wire-to-Wire**

Centerline **5.08 mm [.2 in]**

Number of Positions **2**

Number of Rows **1**

Housing Material **Polyester GF**

Product Drawings

WIRE TO WIRE TAB HSG FOR DYNAMIC

PDF
English

CAD Files

Customer View Model

2D_DXF.ZIP
English

3D PDF

PDF
3D

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Catalog Pages/Data Sheets

D3000 Series Dynamic Connectors Continued

PDF
English

1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH

PDF
English

Product Specifications

Product Specification

Dynamic Connector D-3000 Series

TIF
Japanese

Dynamic Connector D-3000 Series

PDF
Japanese

Product Type Features	Connector System	Wire-to-Wire
	Connector Style	Plug
	Sealed	No
	Applies To	Wire/Cable
	Series Number	3000
	Glow Wire Rating	Standard Part - Not Glow Wire
	Product Type	Connector
	Connector Type	Housing
Configuration Features	Number of Positions	2
	Number of Rows	1
	Selectively Loaded	No
	Preloaded	No
Electrical Characteristics	Operating Voltage	600 VAC [600 VDC]
Body Features	Sealable	No
Contact Features	Contact Type	Tab
	Contact Layout	Inline
	Shunts/Shorting Bars	Without
	Multiple Contact Types	Without
Mechanical Attachment	Panel Mount Retention	Without
Housing Features	Centerline	5.08 mm [.2 in]
	Housing Material	Polyester GF
	Housing Color	Black
Dimensions	Length	23.03 mm [.906 in]
	Height	33.6 mm [1.322 in]
	Width	12.7 mm [.499 in]
Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
Operation/Application	Halogen Free	Yes

For Use With

Receptacle Housing

Industry Standards	CSA Rating	Certified
	CSA File Number	LR7189
	UL Rating	Recognized
	CSA Certified	Yes
	VDE Tested	No
	UL File Number	E28476
	Agency/Standard	CSA, UL
	UL Flammability Rating	UL 94V-0

Packaging Features	Packaging Quantity	250
	Packaging Method	Bag

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

RECTANGULAR CONNECTOR HOUSINGS	RECTANGULAR CONNECTOR HOUSINGS	RECTANGULAR CONNECTOR HOUSINGS	RECTANGULAR CONNECTOR HOUSINGS
DYNAMIC D-3200S TAB HSG 4P K/X 1-179552-4	DYNAMIC 3200 REC HSG 2P SGL 1-178128-2	DYNAMIC D3200 REC HSG 3P SGL Z 3-178128-3	DYNAMIC D-3200 WTW TAB HSG 3P 1-179552-3
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products

Products - 30 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series | Dynamic 3000 Series

DYNAMIC D-3 TAB CONT. L L/P - 175289-3

TE INTERNAL NUMBER: 175289-3

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **250 VAC, 600 VAC**

Contact Retention **With**

Contact Retention Type **Locking Lance**



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series | Dynamic 3000 Series

DYNAMIC D-3 TAB CONT. S 28-24 - 175284-3

TE INTERNAL NUMBER: 175284-3

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **250 VAC, 600 VAC**

Contact Retention **With**

Contact Retention Type **Locking Lance**



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series | Dynamic 3000 Series

DYNAMIC D-3 TAB CONT. M 24-20 - 175285-3

TE INTERNAL NUMBER: 175285-3

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **250 VAC, 600 VAC**

Contact Retention **With**

Contact Retention Type **Locking Lance**

