



CONNECTOR HOUSINGS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

DYNAMIC D-3200S TAB HSG 4P K/X

[Dynamic Series](#) | [Dynamic 3000 Series](#)

1-179552-4

TE Internal Number: 1-179552-4

Always EU RoHS/ELV Compliant

Connector System **Wire-to-Wire**

Centerline **5.08 mm [.2 in]**

Number of Positions **4**

Number of Rows **1**

Housing Material **Polyester GF**

Product Drawings

[WIRE TO WIRE TAB HSG FOR DYNAMIC](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[D3000 Series Dynamic Connectors Continued](#)

PDF
English

[1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH](#)

PDF
English

Product Specifications

Product Specification

[Dynamic Connector D-3000 Series](#)

TIF
Japanese

[Dynamic Connector D-3000 Series](#)

PDF
Japanese

Product Type Features	Connector System	Wire-to-Wire
	Connector Style	Plug
	Sealed	No
	Applies To	Wire/Cable
	Series Number	3000
	Glow Wire Rating	Standard Part - Not Glow Wire
	Product Type	Connector
	Connector Type	Housing
Configuration Features	Number of Positions	4
	Number of Rows	1
	Selectively Loaded	No
	Preloaded	No
Electrical Characteristics	Operating Voltage	600 VAC [600 VDC]
Body Features	Sealable	No
Contact Features	Contact Type	Tab
	Contact Layout	Inline
	Shunts/Shorting Bars	Without
	Multiple Contact Types	Without
Mechanical Attachment	Panel Mount Retention	Without
Housing Features	Centerline	5.08 mm [.2 in]
	Housing Material	Polyester GF
	Housing Color	Black
Dimensions	Length	33.19 mm [1.306 in]
	Height	33.6 mm [1.322 in]
	Width	12.7 mm [.499 in]
Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
Operation/Application	Halogen Free	Yes

For Use With

Receptacle Housing

Industry Standards

CSA Rating

Certified

CSA File Number

LR7189

UL Rating

Recognized

CSA Certified

Yes

VDE Tested

No

UL File Number

E28476

Agency/Standard

CSA, UL

UL Flammability Rating

UL 94V-0

Packaging Features

Packaging Quantity

150

Packaging Method

Bag

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

Products - 30 Results

[View All](#)

Compare 0/10

Relation Type

RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)

PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series | Dynamic 3000 Series

**DYNAMIC D-3 TAB
CONT. S 28-24**

- 175284-3

TE INTERNAL NUMBER: 175284-3

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **250 VAC, 600
VAC**

Contact Retention **With**

Contact Retention Type **Locking
Lance**

RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series I Dynamic 3000 Series

DYNAMIC D-3 TAB
CONT. 2L 16-14
- 917485-5

TE INTERNAL NUMBER: 917485-5

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Tin**

Contact Termination Area Plating

Material **Tin**

Operating Voltage **250 VAC, 600 VAC**

Contact Retention **With**



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series I Dynamic 3000 Series

DYNAMIC D-3 TAB
CONT. L/P 2L - 917512-5

TE INTERNAL NUMBER: 917512-5

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Tin**

Contact Termination Area Plating

Material **Tin**

Operating Voltage **250 VAC, 600 VAC**

Contact Retention **With**

