



CONNECTOR HOUSINGS



✓ Active

[↓](#) **PRODUCT DRAWING**
Japanese

[↓](#) **3D PDF**

TE CONNECTIVITY (TE)

DYNAMIC D-3200S TAB HSG 2P K/X

[Dynamic Series](#) | [Dynamic 3000 Series](#)

1-179553-2

TE Internal Number: 1-179553-2

Always EU RoHS/ELV Compliant

Connector System **Wire-to-Panel, Wire-to-Wire**

Centerline **5.08 mm [.2 in]**

Number of Positions **2**

Number of Rows **1**

Housing Material **Polyester GF**

Product Drawings

[WIRE TO WIRE TAB HSG FOR DYNAMIC D-3200S PANEL MOUNT TYPE](#)

PDF
Japanese

CAD Files

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

Catalog Pages/Data Sheets

[D3000 Series Dynamic Connectors Continued](#)

PDF
English

[1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH](#)

PDF
English

Product Specifications

Product Specification

[Dynamic Connector D-3000 Series](#)

TIF
Japanese

[Dynamic Connector D-3000 Series](#)

PDF
Japanese

Product Environmental Compliance

TE Material Declaration

[MD_1-179553-2_01022014952_dmtec](#)

PDF
English


Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector System	Wire-to-Panel, Wire-to-Wire
	Connector Style	Plug
	Sealed	No
	Applies To	Panel, Wire/Cable
	Series Number	3000
	Glow Wire Rating	Standard Part - Not Glow Wire
	Product Type	Connector
	Connector Type	Housing
Configuration Features	Number of Positions	2
	Number of Rows	1
	Selectively Loaded	No
	Preloaded	No
Electrical Characteristics	Operating Voltage	600 VAC [600 VDC]
Body Features	Sealable	No
Contact Features	Contact Type	Tab
	Contact Layout	Inline
	Shunts/Shorting Bars	Without
	Multiple Contact Types	Without
Mechanical Attachment	Panel Mount Retention Type	Screw Mount
	Panel Mount Retention	With
Housing Features	Centerline	5.08 mm [.2 in]
	Housing Material	Polyester GF
	Housing Color	Black
Dimensions	Length	36.83 mm [1.449 in]
	Height	33.6 mm [1.322 in]
	Width	12.7 mm [.499 in]

Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
Operation/Application	Halogen Free	Yes
	For Use With	Receptacle Housing
Industry Standards	CSA Rating	Certified
	CSA File Number	LR7189
	UL Rating	Recognized
	CSA Certified	Yes
	VDE Tested	No
	UL File Number	E28476
	Agency/Standard	CSA, UL
	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	300
	Packaging Method	Bag
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

RECTANGULAR CONNECTOR HOUSINGS




3.81 DYNAMIC CAP HSG
PANEL 6P
178803-3

Save to List

Find Similar Products

RECTANGULAR CONNECTOR HOUSINGS




DYNAMIC 3200 TAB HSG
20P
1-179555-8

Save to List

Find Similar Products

RECTANGULAR CONNECTOR HOUSINGS




ME CONN MOLD TYPE
REC. HSG 32POS ASSY
1981921-1

Save to List

Find Similar Products

I/O CONNECTOR CONTACTS



DYNAMIC D-3 TAB CONT.
M L/P
175288-2

Save to List


Find Similar Products

RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series I Dynamic 3000 Series

**DYNAMIC D-3 TAB
CONT. M L/P - 175288-2**

TE INTERNAL NUMBER: 175288-2

✓ Active

[Always EU RoHS/ELV Compliant](#)

Contact Type **Tab**


Contact Mating Area Plating

Material **Gold**

Operating Voltage **250 VAC, 600 VAC**

Contact Retention **With**

Contact Retention Type **Locking Lance**




RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series I Dynamic 3000 Series

**DYNAMIC D-3 TAB
CONT. L 20-16
- 175286-2**

TE INTERNAL NUMBER: 175286-2

✓ Active

[Always EU RoHS/ELV Compliant](#)

Contact Type **Tab**


Contact Mating Area Plating

Material **Gold**

Operating Voltage **250 VAC, 600 VAC**

Contact Retention **With**

Contact Retention Type **Locking Lance**




RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series I Dynamic 3000 Series

**DYNAMIC D-3 TAB
CONT. L L/P - 175289-3**

TE INTERNAL NUMBER: 175289-3

✓ Active

[Always EU RoHS/ELV Compliant](#)

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **250 VAC, 600 VAC**

Contact Retention **With**

Contact Retention Type **Locking Lance**

