



CONNECTOR HOUSINGS



✓ Active

↓ **PRODUCT DRAWING**
Japanese

↓ **3D PDF**

TE CONNECTIVITY (TE)

DYNAMIC D-3200 WTW TAB HSG 3P

[Dynamic Series](#) | [Dynamic 3000 Series](#)

1-179553-3

TE Internal Number: 1-179553-3

Always EU RoHS/ELV Compliant

Connector System **Wire-to-Panel, Wire-to-Wire**

Centerline **5.08 mm [.2 in]**

Number of Positions **3**

Number of Rows **1**

Housing Material **Polyester GF**

Product Drawings

[WIRE TO WIRE TAB HSG FOR DYNAMIC D-3200S PANEL MOUNT TYPE](#)

PDF
Japanese

CAD Files

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

Catalog Pages/Data Sheets

[D3000 Series Dynamic Connectors Continued](#)

PDF
English

[1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH](#)

PDF
English

Product Specifications

Product Specification

[Dynamic Connector D-3000 Series](#)

TIF
Japanese

[Dynamic Connector D-3000 Series](#)

PDF
Japanese

Application Specification

[DYNAMIC Series D-3, Crimp-In Type Contacts](#)

TIF
Japanese

[DYNAMIC Series D-3, Crimp-In Type Contacts](#)

PDF
Japanese

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

| | | |
|-----------------------|------------------|--------------------------------------|
| Product Type Features | Connector System | Wire-to-Panel, Wire-to-Wire |
| | Connector Style | Plug |
| | Sealed | No |
| | Applies To | Panel, Wire/Cable |
| | Series Number | 3000 |
| | Glow Wire Rating | Standard Part - Not Glow Wire |
| | Product Type | Connector |
| | Connector Type | Housing |

| | | |
|------------------------|---------------------|-----------|
| Configuration Features | Number of Positions | 3 |
| | Number of Rows | 1 |
| | Selectively Loaded | No |
| | Preloaded | No |

| | | |
|----------------------------|-------------------|----------------------------|
| Electrical Characteristics | Operating Voltage | 600 VAC [600 VDC] |
|----------------------------|-------------------|----------------------------|

| | | |
|---------------|----------|-----------|
| Body Features | Sealable | No |
|---------------|----------|-----------|

| | | |
|------------------|------------------------|----------------|
| Contact Features | Contact Type | Tab |
| | Contact Layout | Inline |
| | Shunts/Shorting Bars | Without |
| | Multiple Contact Types | Without |

| | | |
|-----------------------|----------------------------|--------------------|
| Mechanical Attachment | Panel Mount Retention Type | Screw Mount |
| | Panel Mount Retention | With |


| | | |
|------------------|------------------|--------------------------|
| Housing Features | Centerline | 5.08 mm [.2 in] |
| | Housing Material | Polyester GF |
| | Housing Color | Black |

| | | |
|------------|--------|------------------------------|
| Dimensions | Length | 41.91 mm [1.649 in] |
| | Height | 33.6 mm [1.322 in] |
| | Width | 12.7 mm [.499 in] |

| | | |
|-----------------------|--|------------------------------------|
| Usage Conditions | Operating Temperature Range | -55 – 105 °C [-67 – 221 °F] |
| Operation/Application | Halogen Free | Yes |
| | For Use With | Receptacle Housing |
| Industry Standards | CSA Rating | Certified |
| | CSA File Number | LR7189 |
| | UL Rating | Recognized |
| | CSA Certified | Yes |
| | VDE Tested | No |
| | UL File Number | E28476 |
| | Agency/Standard | CSA, UL |
| Packaging Features | Packaging Quantity | 250 |
| | Packaging Method | Bag |
| Product Compliance | Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE | |

CUSTOMERS ALSO BOUGHT


WIRE-TO-BOARD HEADERS & RECEPTACLES



V-TYPE E.I.S. CONN. 7P ASSY
171825-7

[Save to List](#)
[Find Similar Products](#)


I/O CONNECTOR CONTACTS



DYNAMCI D-3 TAB CONT. L L/P
175289-2

[Save to List](#)
[Find Similar Products](#)


RECTANGULAR CONNECTOR HOUSINGS



3.81 DYNAMIC REC HSG 10P D--D
178289-5

[Save to List](#)
[Find Similar Products](#)

OCEAN APPLICATORS



CRIMPER, WIRE 721488-2

[Save to List](#)
[Find Similar Products](#)

Products - 30 Results

[View All](#)

[Compare 0/10](#)

Relation Type



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series I Dynamic 3000 Series

DYNAMIC D-3 TAB CONT. L/P - 175287-3

TE INTERNAL NUMBER: 175287-3

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **250 VAC, 600 VAC**

Contact Retention **With**

Contact Retention Type **Locking Lance**



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series I Dynamic 3000 Series

DYNAMIC D-3 TAB L/P 3L 16-14 - 353718-5

TE INTERNAL NUMBER: 353718-5

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Tin**

Contact Termination Area Plating
Material **Tin**

Operating Voltage **600 VAC**

Contact Retention **With**



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series I Dynamic 3000 Series

DYNAMIC D-3 TAB CONT 3L 16-14 - 353716-5

TE INTERNAL NUMBER: 353716-5

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Tin**

Contact Termination Area Plating
Material **Tin**

Operating Voltage **250 VAC, 600 VAC**

Contact Retention **With**

