



CONNECTORS

CONNECTOR HOUSINGS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

DYNAMIC D-3200 WTW TAB HSG 6P

[Dynamic Series](#) | [Dynamic 3000 Series](#)

1-179555-3

TE Internal Number: 1-179555-3

[Always EU RoHS/ELV Compliant](#)

Connector System **Wire-to-Panel, Wire-to-Wire**

Centerline **5.08 mm [.2 in]**

Row-to-Row Spacing **7.62 mm [.299 in]**

Number of Positions **6**

Number of Rows **2**



Product Drawings

[WIRE TO WIRE TAB HSG FOR DYNAMIC D-3200M PANEL MOUNT TYPE](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

Catalog Pages/Data Sheets

[D3000 Series Dynamic Connectors Continued](#)

PDF
English

[1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH](#)

PDF
English

Product Specifications

Product Specification	Dynamic Connector D-3000 Series TIF Japanese
Application Specification	Dynamic Connector D-3000 Series PDF Japanese DYNAMIC Series D-3, Crimp-In Type Contacts TIF Japanese DYNAMIC Series D-3, Crimp-In Type Contacts PDF Japanese

Product Environmental Compliance

TE Material Declaration	MD_1-179555-3_062020111139 PDF English
-------------------------	---

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector System	Wire-to-Panel, Wire-to-Wire
	Row-to-Row Spacing	7.62 mm [.299 in]
	Connector Style	Plug
	Sealed	No
	Applies To	Panel, Wire/Cable
	Series Number	3000
	Glow Wire Rating	Standard Part - Not Glow Wire
	Product Type	Connector
	Connector Type	Housing

Configuration Features	Number of Positions	6
	Number of Rows	2
	Selectively Loaded	No
	Preloaded	No

Electrical Characteristics	Operating Voltage	600 VAC [600 VDC]
----------------------------	-------------------	----------------------------

Body Features	Sealable	No
---------------	----------	-----------

Contact Features	Contact Type	Tab
	Contact Layout	Matrix
	Shunts/Shorting Bars	Without

	Multiple Contact Types	Without
Mechanical Attachment	Panel Mount Retention Type	Screw Mount
	Panel Mount Retention	With
Housing Features	Centerline	5.08 mm [.2 in]
	Housing Material	Polyester GF
	Housing Color	Black
Dimensions	Length	41.91 mm [1.649 in]
	Height	33.6 mm [1.322 in]
	Width	20.32 mm [.799 in]
Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
Operation/Application	Halogen Free	Yes
	For Use With	Receptacle Housing
Industry Standards	CSA Rating	Certified
	CSA File Number	LR7189
	UL Rating	Recognized
	CSA Certified	Yes
	VDE Tested	No
	UL File Number	E28476
	Agency/Standard	CSA, UL
	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	150
	Packaging Method	Bag
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

