



1-2232263-1 Product Details



1-2232263-1

Power Triple Lock Connector System

Not reviewed for RoHS Compliance

Product Highlights:


- Power Triple Lock Product Line
- Wire-to-Panel
- Applies To Panel
- Connector
- Housing

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

TE Internal Number: 1-2232263-1



[Add to My Part List](#) |
 [Request Sample](#) |
 [Find Similar Products](#) |
 [Buy Product](#)

Documentation & Additional Information	
Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.	Related Products: <ul style="list-style-type: none"> • Tooling

Product Features (Please use the Product Drawing for all design activity)

<p>Product Type Features:</p> <ul style="list-style-type: none"> • Product Line = Power Triple Lock • Product Type = Connector • Connector Type = Housing <p>Mechanical Attachment:</p> <ul style="list-style-type: none"> • Panel Mount Retention = With • Mount = Panel • Mating Retention Type = Latching • Panel Mount Retention Type = Mounting Ear(s) <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Operating Voltage (VAC) = 600 • Operating Voltage (VDC) = 600 <p>Dimensions:</p> <ul style="list-style-type: none"> • Panel Thickness (mm [in]) = 1.00 - 2.00 [0.039 - 0.079] <p>Body Features:</p> <ul style="list-style-type: none"> • Mating Retention = With <p>Contact Features:</p> <ul style="list-style-type: none"> • Contact Type = Pin • Contact Layout = In-Line <p>Housing Features:</p> <ul style="list-style-type: none"> • Connector Style = Receptacle • Centerline (mm [in]) = 6.00 [0.236] • Housing Material = PBT - GF • Housing Color = Black 	<p>Configuration Features:</p> <ul style="list-style-type: none"> • Number of Positions = 2 <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = Not reviewed for ELV/RoHS compliance • UL Flammability Rating = UL 94V-0 <p>Identification Marking:</p> <ul style="list-style-type: none"> • Keying = A <p>Environmental:</p> <ul style="list-style-type: none"> • Operating Temperature (°C [°F]) = -55 - +105 [-67 - +221] • Halogen Free = No <p>Conditions for Usage:</p> <ul style="list-style-type: none"> • Applies To = Panel • Glow Wire Rating = Glow Wire • For Use With = Plug Housing <p>Operation/Application:</p> <ul style="list-style-type: none"> • Application Use = Wire-to-Panel <p>Packaging Features:</p> <ul style="list-style-type: none"> • Packaging Quantity = 2,300 • Packaging Method = Bag <p>Other:</p> <ul style="list-style-type: none"> • Brand = TE Connectivity
---	---

Feedback

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)
- [AODA Multi-Year Accessibility Plan](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed



