



CONNECTOR HOUSINGS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

DYNAMIC D-5200S TAB HSG 2P K/X

[Dynamic Series](#) | [Dynamic 5000 Series](#)

1-353047-2

TE Internal Number: 1-353047-2

Always EU RoHS/ELV Compliant

Connector System **Wire-to-Panel, Wire-to-Wire**

Insertion Force **9.8 Newton**

Centerline **10.16 mm [.399 in]**

Number of Positions **2**

Number of Rows **1**

Product Drawings

[SINGLE ROW TAB HSG \(PANEL MOUNT\) DYNAMIC D-5200S](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[D4000 And D5000 Series Dynamic Connectors](#)

PDF
English

[1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH](#)

PDF
English

Product Specifications

Product Specification

[Dynamic Connector D-5000 Series](#)

PDF
English

Application Specification

[Dynamic Connector D-5000 Series](#)

PDF
Japanese

Product Environmental Compliance

TE Material Declaration

[MD_1-353047-2_050620152147_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector System	Wire-to-Panel, Wire-to-Wire
	Insertion Force	9.8 Newton
	Connector Style	Plug
	Sealed	No
	Applies To	Panel, Wire/Cable
	Series Number	5000
	Glow Wire Rating	Standard Part - Not Glow Wire
	Product Type	Connector
	Connector Type	Housing

Configuration Features	Number of Positions	2
	Number of Rows	1
	Selectively Loaded	No
	Preloaded	No

Electrical Characteristics	Operating Voltage	630 VAC [630 VDC]
----------------------------	-------------------	----------------------------

Body Features	Sealable	No
---------------	----------	-----------

Contact Features	Contact Type	Tab
	Contact Layout	Inline
	Shunts/Shorting Bars	Without
	Multiple Contact Types	Without

Mechanical Attachment	Panel Mount Retention Type	Screw Mount
	Panel Mount Retention	With





Housing Features	Centerline	10.16 mm [.399 in]
	Housing Material	Polyester GF
	Housing Color	Black

Dimensions	Length	47 mm [1.85 in]
	Height	47 mm [1.85 in]

	Width	16.54 mm [.651 in]
Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
Operation/Application	Halogen Free	Yes
	For Use With	Receptacle Housing
Industry Standards	CSA Rating	Certified
	CSA File Number	LR7189
	UL Rating	Recognized
	CSA Certified	Yes
	VDE Tested	No
	UL File Number	E28476
	Agency/Standard	CSA, UL
	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	100
	Packaging Method	Bag

Product Compliance [Statement of Compliance PDF](#)
[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

MOTOR TERMINAL HOUSINGS	RECTANGULAR CONNECTOR HOUSINGS	RECTANGULAR CONNECTOR HOUSINGS	I/O CONNECTOR CONTACTS
			
FASTON ISOLIERH 2, 8 925387-2	DYNAMIC D-5200S REC HSG 2P K/X 1-179958-2	DYNAMIC D-5200S REC HSG 2P K/Y 2-179958-2	DYNAMIC D-3 REC CONT/L AU 0.76 1-175196-3
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products

Products - 9 Results

[View All](#) [Compare 0/10](#)

Relation Type



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series I Dynamic 5000 Series

**DYNAMIC D-5 TAB
CONT. M L/P - 917805-2**

TE INTERNAL NUMBER: 917805-2

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **630 VAC**

Contact Retention **With**

Contact Retention Type **Locking
Lance**



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series I Dynamic 5000 Series

**DYNAMIC D-5 TAB
CONT. S L/P - 917804-3**

TE INTERNAL NUMBER: 917804-3

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **630 VAC**

Contact Retention **With**

Contact Retention Type **Locking
Lance**



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - I/O Connector Contacts
Dynamic Series I Dynamic 5000 Series

**DYNAMIC D-5 TAB
CONT. S L/P - 917804-2**

TE INTERNAL NUMBER: 917804-2

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **630 VAC**

Contact Retention **With**

Contact Retention Type **Locking
Lance**

